

400804 AND 400830 DNS CAT6 UTP T3

- EC Verified
- 100% tested acc. to ISO/IEC 11801; EN 50173-1; ANSI/TIA-568-C; IEC332-1
- 25 Year DNS Warranty
- RoHS Compliant
- 400830 White housing
- 400804 Black housing





FEATURES

- 25 year DNS Warranty
- EC Verified
- Variable colors
- 90° angel
- 50psc Box
- 100% tested acc. to ISO/IEC 11801;
 EN 50173-1 Class E
- 110 & Krone Punch Down Tool
- DNS QuickTool Compatible
- 50 Micro-Inch Gold Plated

CONSTRUCTION & PERFORMANCE

Wiring

Jack housing

Insertion Force

Operating Temperature Range

Retention Force

Life Cycles

Electrical (UL1863)

Dielectric withstand voltage

T568A & T568B; 23-26AWG Solid Wire

ABS+PC UL94V-0 400804 Black 400830 white

20N Max.(IEC60603-7-4)

-10 to +60C(ISO/IEC 11801; ANSI/TIA 568C.2)

7,7 kg between Jack and Plug

750 Cycles Min.(ISO/IEC 11801; IEC60603-7-4)

Current 1,5Amp Max;Voltage 150V;


1000VAC RMS 60Hz 1 min.

PERFOMANCE OVERVIEW

Category 6 keystones are manufactured and tested to the Category 6 performance standards defined by the TIA, ISO and EN standards bodies. Actual performance exceeds the required standard.

The keystone is also compatible with Category 5 and 5e components.

KEYSTONE DIMENSIONS



TYPICAL APPLICATIONS

- 1000BASE-T Gigabit Ethernet
 LAN networks
- 100BASE-TX Ethernet
- O 10BASE-TX

DNS WARRANTY SYSTEM

The DNS System Warranty provides a 25-year product and applications warranty. The guarantee covers system and application performance according to EN50173-1:2002, ANSI/TIA/EIA-568-B.2:2002 and ISO/IEC 11801-2 at the time of proper signed application form. The warranty may be applied by the certified DNS Partner.