

# Product data sheet



ENSTO CLAMPO PRO ENSTO

Terminal block Y/G, Al/Cu 50 mm<sup>2</sup>

REF. KE61.3 | EAN. 6418677191848

> [The product details page](#)

## Tehnilised omadused

Connectable conductor cross section fine-strand without cable end sleeve	25 - 35 mm <sup>2</sup>
Connectable conductor cross section fine-strand with cable end sleeve	2.5 - 35 mm <sup>2</sup>
Connectable conductor cross section multi-wired	2.5 - 50 mm <sup>2</sup>
Rated voltage	800 V
Type of electrical connection 1	Screw connection
Type of electrical connection 2	Screw connection
Number of levels	1

Number of clamp positions per level	2
Mounting method	DIN rail (top hat rail) 35 mm
Material insulation body	Thermoplastic
Operating temperature	-5 - 80 °C
Inflammability class of insulation material according to UL94	V2
Explosion-tested version 'Ex e'	No
Colour	Green/yellow

## Dokumentatsioon

### CAD & Disaini spetsifikatsioonid / BIM

→ [3D\\_KE61\\_PK2\\_V1.stp](#) | IFC (5.6Mo)

### Lepingud ja sertifikaadid

→ [CE\\_KE61\\_2024\\_EN.pdf](#) | PDF (0.05Mo)