

Product data sheet



ENSTO

Terminal block Blue, Al/Cu 16 mm²

REF. KE65.2 | EAN. 6438100501532

> [The product details page](#)

Tehnilised omadused

Connectable conductor cross section fine-strand without cable end sleeve	10-10 mm ²
Connectable conductor cross section fine-strand with cable end sleeve	1.5-10 mm ²
Connectable conductor cross section solid-core	1.5-16 mm ²
Connectable conductor cross section multi-wired	1.5-16 mm ²
Rated current In	164 A
Rated voltage	800 V
Type of electrical connection 1	Screw connection
Type of electrical connection 2	Screw connection

Number of levels	1
Number of clamp positions per level	4
Mounting method	DIN rail (top hat rail) 35 mm
Material insulation body	Thermoplastic
Operating temperature	-5-80 °C
Inflammability class of insulation material according to UL94	V2
Explosion-tested version 'Ex e'	No
Colour	Blue

Dokumentatsioon

CAD & Disaini spetsifikatsioonid / BIM

- 3D_EN-KE65.2.stp | IFC (5.6Mo)
- 3D_KE65.stp | IFC (3Mo)

Lepingud ja sertifikaadid

- CE_KE65_2024_EN.pdf | PDF (0.05Mo)