


SPILLO




Part number	303499
Lampholder:	LED
Light Source:	LED
Wattage:	24 W
Finish:	AN-96 / Anthracite gray / Textured
Insulation class:	II
Degree of protection:	IP65
IK-J-xxIP:	IK10 20J xx9
CRI:	70
Kelvin:	4000
Lightsource lumen output:	3485 lm
Luminaire lumen output:	1767 lm
L:	L80
B:	B10
Lifetime:	60000 h
Ta MIN luminaire:	-25°
Ta MAX luminaire:	35°
ULR:	0%
IPEA* (Area Lighting):	B
IPEA* (Cycle/Pedestrian Lighting):	C
IPEA* (Green Areas):	C
IPEA* (Historical Areas):	A
Luminous Intensity Class:	G*3




Description

- Polyester powder coated ISO 9227 die-cast aluminium housing
- Fixing kit for posts Ø 60 - Ø 76 mm made of polyester powder-coated die-cast aluminium
- Anti-ageing silicone gasket
- Waterproof cable gland M25x1.5 for cables Ø 9- Ø 14 mm
- External electrical connection with sealed plug-socket QUICK, complete with cable
- LED versions include 220/240 V 50/60 Hz safety transformer
- Analogue dimmable HF ballast, 1-10 V
- Each LED is coupled with an electronic safety device (NUD) that can by-pass it in case of failure
- Stainless steel external screws
- The "SECURE LIGHT DISTRIBUTION" system guarantees uniform light distribution even in the remote case of LED failures
- Powder polyester painting process optimized against UV rays in 13 different steps ISO 9227
- Class II
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data



Technical drawings



OPTIONAL ACCESSORIES


SPILLO




310403
Pole top adaptor Ø 60 mm
Anthracite gray




310405
Pole top adaptor Ø 76 mm
Anthracite gray



315023
Pole Spillo INT. 3.3 m
Anthracite gray



315024
Pole Spillo F.T. 2.8 m with flange
Anthracite gray



310415
Baseplate Spillo