

Eaton 263423

Catalog Number: 263423

Eaton Moeller series xPole - PL7 MCB. Miniature circuit breaker (MCB), 25 A, 3p, characteristic: D

General specifications



Product Name	Catalog Number
Eaton Moeller series xPole - PL7 MCB	263423
EAN	Product Length/Depth
4015082634230	71 mm
Product Height	Product Width
82 mm	52.8 mm
Product Weight	Compliances
0.36 kg	RoHS conform
Model Code	
PL7-D25/3	

Delivery program

Application

Switchgear for residential
and commercial applications
xPole - Switchgear for
residential and commercial
applications

Number of poles

Three-pole

Number of poles (total)

3

Number of poles (protected)

3

Tripping characteristic

D

Release characteristic

D

Amperage Rating

25 A

Type

Miniature circuit breaker
PL7

Technical data - electrical

Voltage type

AC

Rated operational voltage (Ue) - max

400 V

Rated insulation voltage (Ui)

440 V

Rated impulse withstand voltage (Uimp)

4 kV

Frequency rating - min

50 Hz

Frequency rating - max

60 Hz

Rated switching capacity (IEC/EN 60898-1)

10 kA

Rated short-circuit breaking capacity (EN 60898) at 230 V

10 kA

Rated short-circuit breaking capacity (EN 60898) at 400 V

10 kA

Rated short-circuit breaking capacity (IEC 60947-2) at 230 V

0 kA

Rated short-circuit breaking capacity (IEC 60947-2) at 400 V

0 kA

Overvoltage category

III

Pollution degree

2

Technical data - mechanical

Width in number of modular spacings

3

Built-in depth

70.5 mm

Degree of protection

IP20

Design verification as per IEC/EN 61439 - technical data

Rated operational current for specified heat dissipation (In)

25 A

Heat dissipation per pole, current-dependent

0 W

Equipment heat dissipation, current-dependent

7.7 W

Connectable conductor cross section (solid-core) - min
1 mm²

Connectable conductor cross section (solid-core) - max
25 mm²

Connectable conductor cross section (multi-wired) - min
1 mm²

Connectable conductor cross section (multi-wired) - max
25 mm²

Static heat dissipation, non-current-dependent
0 W

Heat dissipation capacity
0 W

Ambient operating temperature - min
-25 °C

Ambient operating temperature - max
75 °C

Design verification as per IEC/EN 61439

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

Additional information

Current limiting class

3

Features

Additional equipment possible

Special features

Ambient temperature hint: a 1 °C increase results in a 0.5% linear reduction of current carrying capacity

Used with

Miniature circuit breaker

PL7

Lisainfo

Characteristic curve

[eaton-xpole-mm4-6-m-mcb-characteristic-curve-003.jpg](#)

[KL_L7_D](#)

Elektriskeemid

[PLS_3P](#)

[eaton-xpole-mm4-6-m-mcb-wiring-diagram-005.jpg](#)

Joonised

[Mas_PLSM](#)

[eaton-xpole-mm4-6-m-mcb-dimensions.jpg](#)

Joonised

[eaton-xpole-mm4-6-m-mcb-3d-drawing-008.jpg](#)

[PLSM_i2t_d](#)

Kataloogid

[eaton-xpole-pl7-mcb-catalog-ca019068en-en-us.pdf](#)

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

mCAD model

pls_3p.dwg

eaton-cadenas-path-03-geo-pls_3p.3db

eaton-cadenas-front_view-pls_3p_front.pra

pls_3p.stp

eaton-cadenas-side_view-pls_3p_side.pra

Paigaldusjuhised

IL019140ZU

PEP Eco-passport

EATO-00046-V01.01-EN

Vastavusavaldused

DA-DC-03_PL7