

# Eaton 262714

Catalog Number: 262714

Eaton Moeller series xPole - PL7 MCB. Miniature circuit breaker (MCB), 10 A, 1p, characteristic: D

## General specifications



Product Name	Catalog Number
Eaton Moeller series xPole - PL7 MCB	262714
EAN	Product Length/Depth
4015082627140	71 mm
Product Height	Product Width
82 mm	17.6 mm
Product Weight	Compliances
0.12 kg	RoHS conform
Model Code	
PL7-D10/1	

## Delivery program

### Application

Switchgear for residential  
and commercial applications  
xPole - Switchgear for  
residential and commercial  
applications

### Number of poles

Single-pole

### Number of poles (total)

1

### Number of poles (protected)

1

### Tripping characteristic

D

### Release characteristic

D

### Amperage Rating

10 A

### Type

Miniature circuit breaker  
PL7

## Technical data - electrical

### Voltage type

AC

### Rated operational voltage (Ue) - max

230 V

### Rated insulation voltage (Ui)

440 V

### Rated impulse withstand voltage (Uimp)

4 kV

### Frequency rating - min

50 Hz

### Frequency rating - max

60 Hz

### Rated switching capacity (IEC/EN 60898-1)

10 kA

### Rated short-circuit breaking capacity (EN 60898) at 230 V

10 kA

### Rated short-circuit breaking capacity (EN 60898) at 400 V

10 kA

### Rated short-circuit breaking capacity (IEC 60947-2) at 230 V

0 kA

### Rated short-circuit breaking capacity (IEC 60947-2) at 400 V

0 kA

### Overvoltage category

III

### Pollution degree

2

## Technical data - mechanical

### Width in number of modular spacings

1

### Built-in depth

70.5 mm

### Degree of protection

IP20

## Design verification as per IEC/EN 61439 - technical data

### Rated operational current for specified heat dissipation (In)

10 A

### Heat dissipation per pole, current-dependent

0 W

### Equipment heat dissipation, current-dependent

1.5 W

Connectable conductor cross section (solid-core) - min

1 mm<sup>2</sup>

Connectable conductor cross section (solid-core) - max

25 mm<sup>2</sup>

Connectable conductor cross section (multi-wired) - min

1 mm<sup>2</sup>

Connectable conductor cross section (multi-wired) - max

25 mm<sup>2</sup>

Static heat dissipation, non-current-dependent

0 W

Heat dissipation capacity

0 W

Ambient operating temperature - min

-25 °C

Ambient operating temperature - max

75 °C

## Design verification as per IEC/EN 61439

### 10.2.2 Corrosion resistance

Meets the product standard's requirements.

#### 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

#### 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

#### 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

### 10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

### 10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

### 10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

### 10.2.7 Inscriptions

Meets the product standard's requirements.

## 10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

## 10.4 Clearances and creepage distances

Meets the product standard's requirements.

## 10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

## Additional information

### Current limiting class

3

### Features

Additional equipment possible

### Special features

Ambient temperature hint: a 1 °C increase results in a 0.5% linear reduction of current carrying capacity

### Used with

PL7

Miniature circuit breaker

## Lisainfo

### Characteristic curve

[eaton-xpole-mmc4-6-m-mcb-characteristic-curve-003.jpg](#)

[KL\\_L7\\_D](#)

### Elektriskeemid

[eaton-xpole-mmc4-6-m-mcb-wiring-diagram-002.jpg](#)

### Joonised

[Mas\\_PLSM](#)

[eaton-xpole-mmc4-6-m-mcb-dimensions.jpg](#)

### Joonised

[eaton-xpole-mmc4-6-m-mcb-3d-drawing-008.jpg](#)

[PLSM\\_i2t\\_d](#)

### Kataloogid

[eaton-xpole-pl7-mcb-catalog-ca019068en-en-us.pdf](#)

[mCAD model](#)

#### 10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

#### 10.8 Connections for external conductors

Is the panel builder's responsibility.

#### 10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

#### 10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

#### 10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

#### 10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

#### 10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

#### 10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

#### 10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

[pls\\_1p.stp](#)

[eaton-cadenas-path-03-geo-pls\\_1p.3db](#)

[eaton-cadenas-front\\_view-pls\\_1p\\_front.pra](#)

[eaton-cadenas-side\\_view-pls\\_1p\\_side.pra](#)

[pls\\_1p.dwg](#)

[Paigaldusjuhised](#)

[IL019140ZU](#)

[PEP Eco-passport](#)

[EATO-00046-V01.01-EN](#)

[Vastavusavaldused](#)

[DA-DC-03\\_PL7](#)