

# Product datasheet

Specifications



## EVlink Wallbox - 11 kW - T2 socket outlet with shutter - charging station

EVH2S11P04K

⚠ Discontinued on: 8 Aug 2024

⚠ To be end-of-service on: 31 Dec 2025

⚠ Discontinued

### Main

|                           |                               |
|---------------------------|-------------------------------|
| Range                     | EVlink                        |
| product name              | EVlink Wallbox                |
| Product or component type | Charging station              |
| Device short name         | EVH2                          |
| Poles description         | 3P + N                        |
| Mounting mode             | Wall-mounted                  |
| Offer type                | Standard                      |
| Max power                 | 11 kW 16 A                    |
| Number of charge point    | 1                             |
| Connection to the vehicle | Socket-outlet T2 with shutter |
| Access control system     | Key                           |

### Complementary

|                        |   |
|------------------------|---|
| rated supply voltage   | 380...415 V AC 50/60 Hz   |
| Earthing system        | TT<br>TN  |
| Number of inputs       | 1   |
| Input type             | Contact for power limitation<br>Contact for delayed charging                      |
| Control type           | 1 white button, function: stop/restart<br>Green button, function: cable unlocking |
| Local signalling       | 1 multi-colour LED, function: status indication                                   |
| Height                 | 480 mm  |
| Width                  | 331.5 mm  |
| Depth                  | 170 mm  |
| Product weight         | 5.6 kg  |
| Colour                 | White (RAL 9003)<br>Grey (RAL 7016)   |
| Standards              | IEC 61851-1<br>IEC 62196-2<br>IEC 62196-1<br>IEC 61851-22                         |
| Product certifications | CE<br>CB  |

## Environment

|                                       |                              |
|---------------------------------------|------------------------------|
| IP degree of protection               | IP54 conforming to IEC 60529 |
| IK degree of protection               | IK10 conforming to IEC 62262 |
| Ambient air temperature for operation | -30...50 °C                  |
| Ambient air temperature for storage   | -40...80 °C                  |
| relative humidity                     | 5...95 %                     |

## Packing Units

|                              |           |
|------------------------------|-----------|
| Unit Type of Package 1       | PCE       |
| Number of Units in Package 1 | 1         |
| Package 1 Height             | 25.500 cm |
| Package 1 Width              | 53.500 cm |
| Package 1 Length             | 40.000 cm |
| Package 1 Weight             | 7.974 kg  |
| Unit Type of Package 2       | P06       |
| Number of Units in Package 2 | 4         |
| Package 2 Height             | 75.000 cm |
| Package 2 Width              | 60.000 cm |
| Package 2 Length             | 80.000 cm |
| Package 2 Weight             | 40.396 kg |

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

## Use Better

### Materials and Substances

[China RoHS Regulation](#)

[China RoHS declaration](#)

## Use Again

### Repack and remanufacture

[Circularity Profile](#)

[End of Life Information](#)