

















Technical sheet

Industrial weatherproof luminaire

MODUS VLO 6650/7200/7750/8300lm, wide body 1570mm, LED 840, body PC, opal PC cover, IP65, driver 1100/1200/1300/1400mA

Code: VLO8000L2W4NDMULTI

EAN: 8596099166496

This product contains a light source with energy efficiency class C



Luminaire properties

| | • • | | | |
|---|--------------------------------|---------------------------|-------------------------------|---|
| Rated lifetime L80/B50 (h): 80000 Degree of protection (IP): IP65 Color housing: Grey Impact strength: IK07 Suitable for suspended mounting: Yes Material housing: Plastic Light source included: Yes Suitable for wall mounting: Yes Suitable for surface mounting: Yes Rated ambient temperature (°C): Suitable for ceiling mounting: Yes Made in Czech republic: Yes Light source Light source type: LED Color temperature (K): 4000 Color rendering index CRI: 80-89 Replaceability: Replaceable light source professional, replaceable ballast | Product category: | Ceiling / wall luminaires | Effective luminous flux (lm): | 8300 |
| Color housing: Grey Impact strength: Ik07 Suitable for suspended mounting: Material housing: Light source included: Yes Suitable for wall mounting: Yes Rated ambient temperature (°C): Suitable for ceiling mounting: Yes Made in Czech republic: Yes Light source Light source Light source Light source Replaceable light source Replaceable light source professional, replaceable ballast | System power (W): | 59 | Luminaire efficacy (lm/W): | 141 |
| Suitable for suspended mounting: Material housing: Light source included: Yes Suitable for wall mounting: Yes Rated ambient temperature (°C): Suitable for ceiling mounting: Yes Made in Czech republic: Yes Light source Light source Light source Light source Replaceability: Replaceable light source professional, replaceable ballast | Rated lifetime L80/B50 (h): | 80000 | Degree of protection (IP): | IP65 |
| mounting: Material housing: Plastic Light source included: Yes Suitable for wall mounting: Yes Rated ambient temperature (°C): Suitable for ceiling mounting: Yes Made in Czech republic: Yes Light source Light source Light source type: LED Color temperature (K): A000 Replaceable light source professional, replaceable ballast | Color housing: | Grey | Impact strength: | IK07 |
| Light source included: Yes Suitable for wall mounting: Yes Suitable for surface mounting: Yes Rated ambient temperature (°C): Suitable for ceiling mounting: Yes Made in Czech republic: Yes Light source Light source type: LED Color temperature (K): 4000 Color rendering index CRI: 80-89 Replaceability: Replaceable light source professional, replaceable ballast | • | Yes | | |
| Suitable for surface mounting: Yes Rated ambient temperature (°C): Suitable for ceiling mounting: Yes Made in Czech republic: Yes Light source Light source type: LED Color temperature (K): 4000 Color rendering index CRI: 80-89 Replaceability: Replaceable light source professional, replaceable ballast | Material housing: | Plastic | | |
| (°C): Suitable for ceiling mounting: Yes Made in Czech republic: Yes Light source Light source type: LED Color temperature (K): 4000 Color rendering index CRI: 80-89 Replaceability: Replaceable light source professional, replaceable ballast | Light source included: | Yes | Suitable for wall mounting: | Yes |
| Light source Light source type: Color temperature (K): Replaceable light source professional, replaceable ballast | Suitable for surface mounting: | Yes | | 0+40 |
| Light source type: Color rendering index CRI: 80-89 Replaceability: Replaceable light source professional, replaceable ballast | Suitable for ceiling mounting: | Yes | Made in Czech republic: | Yes |
| Color rendering index CRI: 80-89 Replaceability: Replaceable light source professional, replaceable ballast | Light source | | | |
| professional, replaceable ballast | Light source type: | LED | Color temperature (K): | 4000 |
| Light source type: 1990420184004 Energy efficiency class: C | Color rendering index CRI: | 80-89 | Replaceability: | Replaceable light source by professional, replaceable ballast |
| | Light source type: | 1990420184004 | Energy efficiency class: | С |

Optical system

| Optical system: | СО | Light outlet: | Direct |
|------------------------|---|----------------------|---------------|
| Light sharing: | Symmetric | Material cover: | Plastic, opal |
| Dimensions | | | |
| Length (mm): | 1570 | Width (mm): | 136 |
| Height/depth (mm): | 90 | Weight (kg): | 2,3 |
| Electrical values | | | |
| Protection class: | 1 | Voltage type: | AC |
| Type of control gear: | LED operating device current-controlled | Nominal voltage (V): | 220240 |
| Control gear included: | Yes | No dim function: | Yes |
| Indoor use only: | Yes | | |