

Surge Arrester CONT-SA10-24



The screened surge arrester can be connected to CONT630 and CONTB630 connectors. The arrester protects transformers, switchgears and transmission lines against atmospheric and switching over voltages. Set includes three pcs of surge arresters and connection bolt.

- Shear head cable lugs – range taking
- Easy installation – only few components
- Silicone material – easy to apply.

Code CONT-SA10-24
GTIN 6438389104264
Name Surge Arrester
In = 10 kA, Uc = 24 kV, Ur = 30 kV

Technical specifications

Dimensions

Weight	10.4 kg
--------	---------

Features

Rated Voltage (Ur)	30 kV
Continuous operating voltage (Uc)	24 kV
Installed length (L)	340 mm
Arrester Classification-Designation	DH
Nominal discharge current (In)	10 kA
Rated short circuit current (Is)	16 kA

Cable

Material insulation	Polymeric
---------------------	-----------

ETIM

ETIM Class	EC003521
Suitable for indoor use	Yes
Suitable for outdoor use	Yes
Type of plug termination	Other
Connection type conductor	Screw connection
Suitable for number of cores	3
Screened	Yes

Packaging

Carton

Size	1 pce
Depth	398 mm
Height	221 mm
Width	263 mm
Weight	10.676 kg
Volume	23.132954 l

Pallet package

Size	36 pcs
Depth	1200 mm
Height	1034 mm
Width	800 mm
Weight	404.336 kg
Volume	992.64 l