



ENERGY SINGLE-FLEX H 100KG

FALL ARREST LANYARD 1301-F

- CE certified hook
- Approved for 100 kg
- Elastic webbing

Energy Single-Flex is a single fall arrest lanyard with flexible webbing and only one hook.

SEGMENTS

- ✓ General industry
- ✓ MEWPs
- ✓ Scaffolding


ARTICLES

012203006	Cresto, Energy Single-Flex H, 1.9m
-----------	------------------------------------

OVERVIEW

A single fall arrest lanyard provides secure protection when working on skylifts and scaffolding.

Energy Single-Flex has the same functions as Energy Twin-Flex except that it has only one webbing and one hook instead of two. Energy Single-Flex is manufactured as a flexible tube with internal elasticity, which allows you to stretch the line to a maximum length of 1.9 meters. At the beginning of the rope there is an external absorber mounted which is released in case of a fall and catches you. The cover on the absorber can easily be replaced if it becomes dirty or damaged to ensure that the rope underneath is protected in the best way.







SPECIFICATION

PRODUCT PROPERTIES

Attaching connector 1	Oval twist lock carabiner in aluminum, mounted with captive pin
Attaching connector 2	Big aluminum hook with 63 mm opening
Energy absorber	Yes
Fall indicator	Yes
Mechanics	Tear-webbing absorber
Maximum number of users	1
Maximum load (kg)	100.0
Minimum working temperature (c)	-40.0
Maximum working temperature (c)	100.0
Minimum breaking strength - MBS (kN)	15.0
Material	Polyamide

CLASSIFICATION

PPE-category	Category 3
EN-standard	EN 355 : 2002
Notified body	1019, VVUU, a.S., Pikartaske 1337/7 716 07 Ostrava - Radvanice Czech Republic

ANNUAL INSPECTION

Annual inspection	Yes, every 12 months
Life span	10 + 2 years. Product lifecycle 10 years + 2 years stock keeping
Warranty	2+1 year when registered in Inspector
Identification	Serial number
RFID	Yes

DOCUMENTS

Declaration of Conformity	Yes
Manual languages	Danish (DA), English (EN), Finnish (FI), French (FR), German (DE), Greek (EL), Norwegian (NO), Spanish (ES), Swedish (SV)



IMAGES







