

Heat shrink trans joint addkit SJA2



The additional kit is used together with the 1 kV joint kit SJK for jointing of belted paper insulated, aluminium sheathed 3 core cables (e.g. APAKM). The kit is suitable for transition from paper insulated cable to plastic insulated. The kit includes three heat shrink tubes for protection of the paper insulation, a heat shrink breakout, a piece of H07V-K cable for jointing the aluminium sheaths.

Code	SJA2
GTIN	6418677445682
Name	Heat shrink trans joint addkit 0,6/1 (1,2) kV 3x/Al-4x50-95 mm ² paper three core with Al sheath to plastic four core for SJK

Technical specifications

Basic kit	SJK2C
Connectors	1 x SLJ2.27
Weight	0.705 kg
Conductor size	Al/Cu 50-95
ETIM	
ETIM Class	EC001169
Rated voltage U0/U (Um)	0.6/1 (1.2) kV
Model	Heat-shrink
Insulating material	Plastic
For connection of paper- with plastic insulated cables	Yes
Number of conductors	3
Nominal cross section conductor	50 ... 95 mm²
Connection accessories included	None
Halogen free	Yes

Packaging

Carton	
Size	5 pcs
Depth	403 mm
Height	246 mm
Width	298 mm
Weight	3.858 kg
Volume	29.543124 l
Pallet package	
Size	160 pcs
Depth	1200 mm
Height	1154 mm
Width	800 mm
Weight	143.456 kg
Volume	1107.84 l