


# Cold shrink indoor term CIT1.2402L



Cold shrink indoor termination for 1-core cables with Al/Cu conductor, polymeric insulation and Cu-wire screen. The kit contains components for three cable cores. Mechanical lugs for conductor and screen wire connection are included in the kit. The termination kits include cold shrinkable termination bodies with integrated geometric stress control elements and all the additional components needed for assembly.

- Easy installation – most critical components integrated in one body
- Spiral technology – easy to apply to a wide range of cables
- Integrated geometric stress control – most reliable operation in all networks
- No special tools needed
- Adapts to temperature variations.

**Code** CIT1.2402L  
**GTIN** 6438100301132  
**Name** Cold shrink indoor term  
12.7/22 (24) kV 10-95 mm<sup>2</sup> 3x1-core with lug

## Technical specifications

Weight	1.39 kg
Rated voltage U <sub>0</sub> /U (Um)	12.7/22 (24) kV
Screen/shield connection	6 ... 50 mm <sup>2</sup>
Creepage distance	370 mm
Shed diameter	58 mm
Shrink technique	Cold shrink
Installed length (L)	310 mm
Accessory type	Termination, indoor
Conductor material	Al/Cu
Conductor size round	10 ... 95 mm <sup>2</sup>
Diameter on the insulation	13.8 ... 27 mm
Diameter outer sheath	22 ... 38 mm
Material insulation	Polymeric
Material screen/shield	Cu-wire
Conductor size Um = 12 kV	35 ... 95 mm <sup>2</sup>
Number of cores	3
Conductor size Um = 24 kV	10 ... 95 mm <sup>2</sup>
Installation temperature	-25 ... 50 °C
Operating temperature	-50 ... 90 °C
Storage temperature	5 ... 40 °C

## ETIM

ETIM Class	EC003520
Number of cores	3
Suitable for indoor use	Yes
Suitable for outdoor use	No
Type of cable termination	Cold-shrink
Insulating material	Plastic
	Yes
Cable lug included	Yes
Shape of cable lug	Screw connection
Nominal cross section	10 ... 95 mm <sup>2</sup>

Packaging

Plastic bag

Size	1 pce
Height	0.5 mm
Width	250 mm
Weight	1.490 kg

Carton

Size	1 pce
Depth	375 mm
Height	115 mm
Width	250 mm
Weight	1.706 kg
Volume	10.78125 l

Pallet package

Size	63 pcs
Depth	1200 mm
Height	1050 mm
Width	800 mm
Weight	127.478 kg
Volume	1008 l