

Heat shrink joint SJK25C



The joint kit is used for jointing 1 kV cables with plastic insulation and plastic outer sheath. The kit is suitable for 4 to 4 core and 4 to 3+1 core cables. The kit includes four screw connectors suitable both for aluminium and copper conductors, grinding and cleaning materials, four heat shrink tubes for insulation and one for outer protection.

Code	SJK25C
GTIN	6438389019650
Name	Heat shrink joint 0,6/1 (1,2)kV 70-150mm ² 4-core with connectors

Technical specifications

Rated voltage U0/U (Um)	0.6/1 (1,2) kV
Installed length (L)	650 mm
Shrink technique	Heat shrink
Connectors	4 x SLJ2.27
Accessory type	Straight through joint
Conductor material	Al/Cu
Conductor size round	70 ... 150 mm ²
Number of cores	4
Material insulation	Polymeric
Weight	1.45 kg
Installation temperature	-25 ... 50 °C
Operating temperature	-50 ... 90 °C
Storage temperature	5 ... 40 °C

ETIM

ETIM Class	EC001169
Rated voltage U0/U (Um)	0.6/1 (1.2) kV
Model	Heat-shrink
Insulating material	Plastic
For connection of paper- with plastic insulated cables	No
Number of conductors	4
Nominal cross section conductor	70 ... 150 mm ²
Connection accessories included	Screw connector with shear-off head
Halogen free	Yes

Packaging

Pallet package

Size	50 pcs
Depth	1180 mm
Height	900 mm
Width	780 mm
Weight	76.700 kg
Volume	828.36 l