

Heat shrink trans joint addkit SJA1



The additional kit is used together with the 1 kV joint kit SJK for jointing of belted paper insulated, aluminium sheathed 3 core cables (e.g. APAKM). The kit is suitable for transition from paper insulated cable to plastic insulated. The kit includes three heat shrink tubes for protection of the paper insulation, a heat shrink breakout, a piece of H07V-K cable for jointing the aluminium sheaths.

| | |
|-------------|---|
| Code | SJA1 |
| GTIN | 6418677445675 |
| Name | Heat shrink trans joint addkit 0,6/1 (1,2) kV 3x/Al-4x16-50 mm ² paper three core with Al sheath to plastic four core for SJK |

Technical specifications

| | |
|----------------|-------------|
| Basic kit | SJK1C |
| Connectors | 1 x SLJ2.27 |
| Weight | 0.712 kg |
| Conductor size | Al/Cu 16-50 |

ETIM

| | |
|--|----------------|
| ETIM Class | EC001169 |
| Rated voltage U0/U (Um) | 0.6/1 (1.2) kV |
| Model | Heat-shrink |
| Insulating material | Plastic |
| For connection of paper- with plastic insulated cables | Yes |
| Number of conductors | 3 |
| Nominal cross section conductor | 16 ... 50 mm² |
| Connection accessories included | None |
| Halogen free | Yes |

Packaging

Carton

| | |
|--------|-------------|
| Size | 5 pcs |
| Depth | 403 mm |
| Height | 246 mm |
| Width | 298 mm |
| Weight | 3.893 kg |
| Volume | 29.543124 l |

Pallet package

| | |
|--------|------------|
| Size | 120 pcs |
| Depth | 1200 mm |
| Height | 1020 mm |
| Width | 800 mm |
| Weight | 113.432 kg |
| Volume | 979.2 l |