

# Surge Arrester CONT-SA10-12



The screened surge arrester can be connected to CONT630 and CONTB630 connectors. The arrester protects transformers, switchgears and transmission lines against atmospheric and switching over voltages. Set includes three pcs of surge arresters and connection bolt.

- Shear head cable lugs – range taking
- Easy installation – only few components
- Silicone material – easy to apply.

<b>Code</b>	CONT-SA10-12
<b>GTIN</b>	6438389104240
<b>Name</b>	Surge Arrester In = 10 kA, Uc = 12 kV, Ur = 15 kV

## Technical specifications

Weight	8.51 kg
Rated Voltage (Ur)	15 kV
Continuous operating voltage (Uc)	12 kV
Installed length (L)	260 mm
Arrester Classification-Designation	DH
Nominal discharge current (In)	10 kA
Rated short circuit current (Is)	16 kA
Material insulation	Polymeric

### ETIM

ETIM Class	EC003521
Suitable for indoor use	Yes
Suitable for outdoor use	Yes
Type of plug termination	Other
Connection type conductor	Screw connection
Suitable for number of cores	3
Screened	Yes

## Packaging

### Carton

Size	1 pce
Depth	375 mm
Height	157 mm
Width	250 mm
Weight	8.752 kg
Volume	14.71875 l

### Pallet package

Size	45 pcs
Depth	1200 mm
Height	1014 mm
Width	800 mm
Weight	413.840 kg
Volume	973.44 l