



TRIX SN 700

ISO 9001-2015



SA0669-ZB07+BZ05

Reference	Class	Standard	Material	Weight	Sold by Pallet
89466901	D 400	DIN EN 124-2	EN-GJS	ca. 83 kg	5

Locking

- innovative automatic 3 point spring locking system
- hinders unauthorised opening = anti-theft
- through the positioning of the locking points the cover is centred in the frame and is frictionally locked

Frame

- self-levelling / roll-in frame
- becomes an integrated part of the road surface
- lies floating in the bitumen road surface and not on the shaft
- suitable for shafts of dia. 700mm
- clear opening 601mm / inspection opening 650mm

Insert

- changeable dampening HYDROprene-insert
- L-shape hinders vertical and horizontal contact to iron
- Polychloroprene according to DIN 53505 standard
- long life, high abrasion stability for extreme loads


Hinge

- simple ergonomic opening of the cover
- ca. 120° position of inspection, ca. 100° lifting position and blocking against unintentional closing of the cover


Options

- additional locking by means of a turn-buckle

3 point locking system



HYDROpren-insert



HYDROTEC Technologies AG
Düngstruper Strasse 46
27793 Wildeshausen, Germany

 export@hydrotec.com

 www.hydrotec.com

 +49 4431 9355-0

 +49 4431 9355-22