

UCT-TM 3,5 - Marker for terminal blocks



0829484
<https://www.phoenixcontact.com/fr/products/0829484>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Marker for terminal blocks, Sheet, white, unmarked, can be labeled with: BLUEMARK E.CARD, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME 2.0, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, TOPMARK NEO, TOPMARK LASER, mounting type: latching, for terminal block width: 3.5 mm, Number of individual labels: 102, text field height: 10.5 mm, text field width: 2.95 mm

Your advantages

- The UCT-TM... UniCard labeling range includes markers for Phoenix Contact products with tall marker grooves, e.g. terminals
- The markers, which are supplied in uniform sheets, can be marked quickly, easily, and precisely using the card printers
- The sheets provide additional space for project information and function text that can be helpful during further assembly
- The multi-section marking strips are easy to fit and can be easily separated if required
- Marking service: Phoenix Contact can custom-mark all UniCard markers according to your specifications

Commercial data

Item number	0829484
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	BG2118
Product key	BG2118
GTIN	4046356571111
Weight per piece (including packing)	15.5 g
Weight per piece (excluding packing)	13.79 g
Customs tariff number	39269097
Country of origin	PL

UCT-TM 3,5 - Marker for terminal blocks



0829484

<https://www.phoenixcontact.com/fr/products/0829484>

Technical data

Notes

General	Can be labeled via thermal transfer
---------	-------------------------------------

Product properties

Product type	Klemmenmarker
Pitch	3.5 mm

Marking

Number of individual labels	102
Number of individual labels per row	17
Identification technology	Thermotransfer

Dimensions

Width	2.95 mm
Height	10.50 mm
Depth	4.60 mm
Pitch	3.5 mm

Material specifications

Color	white (RAL 9010)
Flammability rating according to UL 94	V0
Base element material	PC
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Components	free from silicone and halogen

Environmental and real-life conditions

Test for substances that would hinder coating with paint or varnish

Result	Test passed
--------	-------------

Test for substances that would hinder coating with paint or varnish

Result	Test passed
Specification	EN ISO 1518-1:2023 (following)
Requirements	≥ 5 N
Result	Test passed

Tesafilm test

Specification	DIN EN ISO 2409:2020-12 (following)
Result	Test passed

UV resistance

Specification	DIN EN ISO 4892-2:2021-11 (following)
---------------	---------------------------------------

UCT-TM 3,5 - Marker for terminal blocks



0829484

<https://www.phoenixcontact.com/fr/products/0829484>

Result	Test passed
Test duration	96 h
Procedure	Artificial irradiation.

Temperature resistance

Specification	ANSI/UL 969-2018:03 (following)
Test duration	240 h
Rating 100 °C (121 °C)	Test passed

Wipe resistance of inscriptions

Specification	DIN EN 61010-1 (VDE 0411-01):2020-03 DIN EN 62208 (VDE 0660-511):2012-06 (in parts)
Isopropyl [CAS No. 67-63-0]	Test passed
n-Hexane [CAS No. 110-54-3]	Test passed
Water + Petroleum ether [CAS No. 64742-82-1]	Test passed
Sodium hydroxide 0.1 mol/l [CAS No. 1310-73-2]	Test passed
Specification	ISO 175:2010 (following)
Test duration	168 h
Diesel [CAS No. 68476-34-6]	Test passed
IRM 901	Test passed
IRM 902	Test passed

Testing in a condensation changing climate in the presence of sulfur dioxide

Specification	EN ISO 22479:2022-06
Result	Test passed
Procedure	Method B
Cycles	2

Salt spray test

Specification	DIN EN IEC 60068-2-11 (VDE 0468-2-11):2022-10
Result	Test passed
Test duration	96 h

Ambient conditions

Ambient temperature (operation)	-40 °C ... 100 °C
Recommended ambient temperature (storage/transport)	23 °C
Recommended humidity (storage/transport)	50 % (Storage in a dry and dark place in the original packaging is recommended)
Shelf life	2 years

Standards and regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------

Standards

UCT-TM 3,5 - Marker for terminal blocks



0829484

<https://www.phoenixcontact.com/fr/products/0829484>

Standards/regulations	EN 45545-2
-----------------------	------------

Mounting

Mounting type	latching
---------------	----------

UCT-TM 3,5 - Marker for terminal blocks



0829484

<https://www.phoenixcontact.com/fr/products/0829484>

Classifications

ECLASS

ECLASS-13.0	27281101
ECLASS-15.0	27281101

ETIM

ETIM 9.0	EC000761
----------	----------

UNSPSC

UNSPSC 21.0	39131500
-------------	----------

UCT-TM 3,5 - Marker for terminal blocks



0829484

<https://www.phoenixcontact.com/fr/products/0829484>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

UCT-TM 3,5 - Marker for terminal blocks



0829484

<https://www.phoenixcontact.com/fr/products/0829484>

Accessories

BLUEMARK E.CARD - Printer

1506732

<https://www.phoenixcontact.com/fr/products/1506732>



Monochrome UV inkjet card printer, with automated material processing, intuitive user guidance via the printer display, data exchange via OPC UA interface and marking software, for marking UC and UCT cards, UM strips, and metal markers.

THERMOMARK CARD 2.0 - Thermal transfer printer

1085267

<https://www.phoenixcontact.com/fr/products/1085267>



The THERMOMARK CARD 2.0 thermal transfer printer prints marking materials in card and sheet format quickly and with high quality. Create high-quality markers for applications in terminal, wire, cable, equipment, and plant marking.

UCT-TM 3,5 - Marker for terminal blocks

0829484

<https://www.phoenixcontact.com/fr/products/0829484>



THERMOMARK PRIME 2.0 - Thermal transfer printer

1472405

<https://www.phoenixcontact.com/fr/products/1472405>



Thermal transfer printer for printing card materials with a print resolution of 300 dpi. Suitable for stationary as well as mobile use thanks a 7" color touch display with integrated "MARKING system app" and a replaceable battery pack.

BLUEMARK ID COLOR - Printer

1002329

<https://www.phoenixcontact.com/fr/products/1002329>



CMYK multicolor printer with UV inkjet technology, with integrated "MARKING system app" identification software, 7" color touch display for printing plastic labels in UC, UCT, US, and UM format, as well as metal labels.

UCT-TM 3,5 - Marker for terminal blocks

0829484

<https://www.phoenixcontact.com/fr/products/0829484>



TOPMARK NEO - Laser marker

1012015

<https://www.phoenixcontact.com/fr/products/1012015>



Laser marking system for the efficient marking of metal or plastic marking material from the LS..., UCT..., UC.../PP..., UM... product families.

THERMOMARK-RIBBON 110/50-TC - Ink ribbon

0801384

<https://www.phoenixcontact.com/fr/products/0801384>



Ink ribbon, for THERMOMARK CARD for printing product groups UCT..., US..., and UM..., length: 50 m, roll length: 50 m, width: 110 mm, color: black

UCT-TM 3,5 - Marker for terminal blocks

0829484

<https://www.phoenixcontact.com/fr/products/0829484>



THERMOMARK-RIBBON 110-TC - Ink ribbon

0801371

<https://www.phoenixcontact.com/fr/products/0801371>



Ink ribbon, for THERMOMARK CARD for printing product groups UCT..., US..., and UM..., length: 300 m, roll length: 300 m, width: 110 mm, color: black

TMP-RIBBON 110 BK 100 - Ink ribbon cartridge

0803374

<https://www.phoenixcontact.com/fr/products/0803374>



Ink ribbon cartridge, for THERMOMARK PRIME for printing product groups UCT. ..., US..., and UM..., roll length: 70 m, width: 110 mm

UCT-TM 3,5 - Marker for terminal blocks

0829484

<https://www.phoenixcontact.com/fr/products/0829484>



BM E.CARD-CARTR. BK 101 - Ink cartridge

1569770

<https://www.phoenixcontact.com/fr/products/1569770>



Ink cartridge including printhead, compatible with BLUEMARK E.CARD, for replacement, color: black

BM E.CARD-CLEANING CARTR. 100 - Cleaning cartridge

1569768

<https://www.phoenixcontact.com/fr/products/1569768>



Cleaning cartridge, for replacement, compatible with BLUEMARK E.CARD

UCT-TM 3,5 - Marker for terminal blocks

0829484

<https://www.phoenixcontact.com/fr/products/0829484>



BM ID-CARTR. CY - Ink cartridge

1044346

<https://www.phoenixcontact.com/fr/products/1044346>



Replacement UV fluid, 23 ml, color: cyan

BM ID-CARTR. MA - Ink cartridge

1044347

<https://www.phoenixcontact.com/fr/products/1044347>



Replacement UV fluid, 23 ml, color: magenta

UCT-TM 3,5 - Marker for terminal blocks

0829484

<https://www.phoenixcontact.com/fr/products/0829484>



BM ID-CARTR. YE - Ink cartridge

1044348

<https://www.phoenixcontact.com/fr/products/1044348>

Replacement UV fluid, 23 ml, color: yellow



BLUEMARK CLED-FLUID-CARTR. - Ink cartridge

5146662

<https://www.phoenixcontact.com/fr/products/5146662>

Cartridge, for replacement, 20 ml UV color, black, including cleaning cartridge



UCT-TM 3,5 - Marker for terminal blocks



0829484

<https://www.phoenixcontact.com/fr/products/0829484>

TMP-UCT-MAG1 - Magazine

0803342

<https://www.phoenixcontact.com/fr/products/0803342>



Magazine, for the THERMOMARK PRIME and the THERMOMARK CARD, for accommodating UCT-TM..., UCT1(U)-TM..., UCT5-TM..., UCT-EM (5x10), UCT-EM (6x10), length: 0.166 m, width: 114 mm, height: 11.5 mm

BM ID-MAG20 - Magazine

1044356

<https://www.phoenixcontact.com/fr/products/1044356>



Infeed magazine for accommodating a max. of 20 UniCard sheets

UCT-TM 3,5 - Marker for terminal blocks

0829484

<https://www.phoenixcontact.com/fr/products/0829484>



BM ID-MAG40 - Magazine

1044357

<https://www.phoenixcontact.com/fr/products/1044357>

Infeed magazine for accommodating a maxi. of 40 UniCard sheets




TOPMARK LASER-MAG UCT-A - Magazine

0803141

<https://www.phoenixcontact.com/fr/products/0803141>

Magazine for the TOPMARK LASER, for accommodating UCT material automatically



UCT-TM 3,5 - Marker for terminal blocks

0829484

<https://www.phoenixcontact.com/fr/products/0829484>



TOPMARK LASER-MAG UCT-M - Magazine

0803143

<https://www.phoenixcontact.com/fr/products/0803143>

Magazine for the TOPMARK LASER, for accommodating UCT material manually



THERMOMARK CARD - Thermal transfer printer

5146464

<https://www.phoenixcontact.com/fr/products/5146464>

Thermal transfer printer for cards



UCT-TM 3,5 - Marker for terminal blocks

0829484

<https://www.phoenixcontact.com/fr/products/0829484>



THERMOMARK PRIME - Thermal transfer printer

5148888

<https://www.phoenixcontact.com/fr/products/5148888>



Mobile thermal transfer printer for card materials, including power supply unit, Euro/US power cable, and USB cable. User manual printed in German and English. Magazine for UCT-TM... sheets and magazine for US-... cards. One packing unit each UCT-TM 6, US-EMLP (85,6x54), ink ribbon cartridge = 70 m

THERMOMARK CARD-UCT-MAG1 - Magazine

5146480

<https://www.phoenixcontact.com/fr/products/5146480>



Magazine for the THERMOMARK CARD printer, for accommodating UCT sheets (UCT-TM..., UCT1-TM..., UCT5-TM...)

UCT-TM 3,5 - Marker for terminal blocks

0829484

<https://www.phoenixcontact.com/fr/products/0829484>



BLUEMARK ID - Printer

1003334

<https://www.phoenixcontact.com/fr/products/1003334>



Monochrome printer with UV inkjet technology and integrated "MARKING system app" identification software. 7" color touch display for printing plastic labels in UC, UCT, US, and UM format, as well as metal labels.

BLUEMARK CLED - Printer

5147999

<https://www.phoenixcontact.com/fr/products/5147999>



Printers with LED-UV technology for printing plastic labels in UniCard format.

Phoenix Contact 2025 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT SAS
52 Boulevard de Beaubourg Emerainville
77436 Marne La Vallée Cedex 2 France
+33 (0) 1 60 17 98 98
documentation@phoenixcontact.fr