

Luminaire with asymetrical reflector

MODUS ASTA 6000, asymetric reflector, 1500mm, surface/pendant, LED840

Code: ASTAP6000L4/ND

EAN: 8596099035945



Luminaire properties

Product category:	Ceiling / wall luminaires	Effective luminous flux (lm):	6500
System power (W):	47	Luminaire efficacy (lm/W):	138
Rated lifetime L80/B50 (h):	80000	Degree of protection (IP):	IP20
Color housing:	White	Suitable for suspended mounting:	Yes
Material housing:	Steel		
Light source included:	Yes		
Suitable for surface mounting:	Yes	Suitable for ceiling mounting:	Yes
Made in Czech republic:	Yes		

Light source

Light source type:	LED	Color temperature (K):	4000
Color rendering index CRI:	80-89	Replaceability:	Replaceable light source by professional, replaceable ballast

Optical system

Optical system:	AS	Light outlet:	Direct
Light sharing:	Asymmetric		

Dimensions

Length (mm):	1486	Width (mm):	100
Height/depth (mm):	67	Weight (kg):	4

Electrical values

Protection class:	I	Connection type:	Pinching contact
Voltage type:	AC	Type of control gear:	LED operating device current-controlled
Nominal voltage (V):	220...240	Control gear included:	Yes
Type of wiring:	Ending	No dim function:	Yes