


385182400060

Relay interface module (EMR or SSR) 0.1 - 2 - 3 - 5 - 6 - 8 - 16 A



This image is for illustrative purposes only and therefore may not represent the exact product code. Colours may vary.

Technical description:

Relay interface modules, Electromechanical relay, with screw terminal, 1 pole, CO (nPDT), 6 A, AgNi, AC coil, 240 V, operating from 184 to 264 V, rated power 0.7 VA, consumption 3 mA, holding voltage 144 V, must drop-out voltage 24 V, option: AC or AC/DC, ambient temperature from -40 to +55 °C

[BROWSE PRODUCT PAGE](#)

Technical Features:

Ambient temperature range:	-40...55 °C
Commercial Description:	Relay Interface Module with single output, width 6,2 mm. Equipped with screw terminals. With AC or DC output circuit and DC input circuit. 35 mm rail (EN 60715) mounting. Designed for interfacing with PLC systems.
Contact configuration:	1 pole, CO (nPDT)
Dimensions:	6.2x88.4x72.1 mm
Electrical life:	60000 cycles
Insulation coil/contacts:	6 kV
Nominal voltage AC:	240 V
Operating range AC:	184...264 V
Rated contact voltage:	250 V AC
Rated current (contacts):	6
Rated power AC:	0.7 VA
Supply:	AC coil
Certifications and quality approvals (according to type):	EACCEUKCA

The information, technical details, data and features contained in this document are subject to change or modification at any time.
It is for information purposes only and does not form the basis of a contract.

Need more information?
[Contact our sales](#) [Find a dealer](#)