

Specifications



Photo is representative



Eaton XTCF032C10F

Eaton XT IEC contactor, 32A, 230 Vac, 50 Hz, 1NO, 32A, Frame C, 45 mm, 50 Hz, 7.5, 7.5, 10, 15 hp (3PH @200, 230, 460, 575 V), Four-pole, Non-reversing, XT IEC series, Screw terminals, Full voltage non-reversing contactor

General specifications

PRODUCT NAME	Eaton XT IEC contactor
CATALOG NUMBER	XTCF032C10F
EAN	4015081093694
PRODUCT LENGTH/DEPTH	4.33 in
PRODUCT HEIGHT	2.48 in
PRODUCT WIDTH	3.86 in
PRODUCT WEIGHT	0.48501698 lb
COMPLIANCES	CE Marked RoHS Compliant
CERTIFICATIONS	UL Listed CSA Certified IEC 60947 EN 60947
CATALOG NOTES	Screw terminals (6-65A); 5 mm (80-150A); no lugs (185-2000A)
PRODUCT TYPE	Contactors

Product specifications

AMPERAGE RATING	32A
HP RATING - MAX	7.5, 7.5, 10, 15 hp (3PH @200,230,460,575 V)
NUMBER OF POLES	Four-pole
TYPE	Full voltage non-reversing contactor
FREQUENCY RATING	50 Hz
TERMINALS	Screw terminals
COIL VOLTAGE	230 Vac, 50 Hz
CONTACT CONFIGURATION	1 NO
CONTINUOUS AMPERE RATING	32 A
SERIES	XT IEC
OPERATION	Non-reversing

Resources

CATALOGS

[Motor Control and Protection, IEC Contactors and Starters, Volume 5, Tab 1](#)

SPECIFICATIONS AND DATASHEETS

[Eaton Specification Sheet - XTCF032C10F](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

