




## PRODUCT-DETAILS

**AUXGM3-11****AUXGM3-11 AUXILIARY CONTACT****General Information**

<b>Extended Product Type:</b>	AUXGM3-11
<b>Product ID:</b>	1SCA162790R1001
<b>EAN:</b>	6417019928272
<b>Catalog Description:</b>	AUXGM3-11 AUXILIARY CONTACT
<b>Long Description:</b>	OT Plus Switch disconnecter series. Auxiliary contact block for DIN mounted OT30... 160G3_series. 1NO and 1NC contact. Snap-on mounting on both sides of the switch. The 1NO has early break function. Including filler part for DIN cut-out.
<b>Display Name:</b>	AUXGM3-11

**Material Compliance**

<b>Conflict Minerals Reporting Template (CMRT):</b>	9AKK108467A5658
<b>REACH Declaration:</b>	1SCC011021D0201
<b>RoHS Declaration:</b>	1SCC011020D0201
<b>RoHS Information:</b>	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

## Popular Downloads

<b>Data Sheet, Technical Information:</b>	9AKK108468A5537 1SCC301020C0201
<b>Instructions and Manuals:</b>	1SCC390188M0201
<b>Mechanical Drawings:</b>	AUXGM3_11.stp

## Environmental

<b>Degree of Protection:</b>	Front IP20
<b>Pollution Degree:</b>	3

## Ordering

<b>Minimum Order Quantity:</b>	1 piece
<b>Customs Tariff Number:</b>	85389099
<b>Country of Origin:</b>	Bulgaria

## Dimensions

<b>Product Net Width:</b>	16.0 mm
<b>Product Net Height:</b>	62.0 mm
<b>Product Net Depth / Length:</b>	59.6 mm
<b>Product Net Weight:</b>	0.030 kg

## Container Information

<b>Package Level 1 Units:</b>	bag 1 piece
<b>Package Level 1 Width:</b>	165 mm
<b>Package Level 1 Depth / Length:</b>	80 mm
<b>Package Level 1 Height:</b>	16 mm
<b>Package Level 1 Gross Weight:</b>	0.035 kg
<b>Package Level 1 EAN:</b>	6417019928272

## Technical

<b>Cable Cross-Section:</b>	Cu 0.75...2.5 mm <sup>2</sup>
<b>Conventional Free-air Thermal Current (<math>I_{th}</math> 16 A):</b>	
<b>Conventional Thermal Current (<math>I_{the}</math>):</b>	16 A
<b>Mounting Type:</b>	Base/DIN mounting
<b>Rated Insulation Voltage (<math>U_i</math>):</b>	acc. to IEC 60947-1 690 V
<b>Recommended Screw Driver:</b>	Main Circuit Pozidriv 2

<b>Terminal Type:</b>	Screw Terminals
<b>Tightening Torque:</b>	acc. IEC 60947-1 0.8 N·m
<b>Wire Stripping Length:</b>	Main Circuit 8-10 mm Main Circuit 0.31-0.39 in

---

### Technical UL/CSA

<b>Wire Size:</b>	18-14 AWG
<b>Tightening Torque UL/CSA:</b>	UL 7 lbf·in

---

### Certificates and Declarations

<b>Declaration of Conformity - CE:</b>	1SCC390103D2701
--	-----------------

---

### External Classifications and Standards

<b>Object Classification Code:</b>	Q
<b>ETIM 9:</b>	EC000041 - Auxiliary contact block
<b>ETIM 10:</b>	EC000041 - Auxiliary contact block
<b>UNSPSC:</b>	39121522
<b>IDEA Granular Category Code (IGCC):</b>	4743 >> Auxiliary contact block
<b>eClass:</b>	V11.1 : 27371302
<b>WEEE Category:</b>	5. Small Equipment (No External Dimension More Than 50 cm)
<b>E-Number (Finland):</b>	3660443
<b>E-Number (Sweden):</b>	3172191

---

### Categories

Products > Low Voltage Products and Systems > Switches > Switch Disconnectors

