



PRODUCT-DETAILS

AUXGD-11**AUXGD-11 AUXILIARY CONTACT****General Information**

| | |
|-------------------------------|--|
| Extended Product Type: | AUXGD-11 |
| Product ID: | 1SCA162595R1001 |
| EAN: | 6417019926216 |
| Catalog Description: | AUXGD-11 AUXILIARY CONTACT |
| Long Description: | OT Plus Switch disconnecter series. Auxiliary contact block for Door mounted OT16... 160G_series. 1NO and 1NC contact. Snap-on mounting on both sides of the switch. The 1NO has early break function. |
| Display Name: | AUXGD-11 |

Material Compliance

| | |
|---|--|
| Conflict Minerals Reporting Template (CMRT): | 9AKK108467A5658 |
| REACH Declaration: | 1SCC011021D0201 |
| RoHS Declaration: | 1SCC011020D0201 |
| RoHS Information: | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |

Popular Downloads

| | |
|---|------------------------------------|
| Data Sheet, Technical Information: | 9AKK108468A5537 1SCC301020C0201 |
| Instructions and Manuals: | 1SCC390188M0201 |
| Mechanical Drawings: | AUXGD_11.stp |

Environmental

| | |
|------------------------------|------------|
| Degree of Protection: | Front IP20 |
| Pollution Degree: | 3 |

Ordering

| | |
|--------------------------------|----------|
| Minimum Order Quantity: | 10 piece |
| Customs Tariff Number: | 85389099 |
| Country of Origin: | Bulgaria |

Dimensions

| | |
|------------------------------------|----------|
| Product Net Width: | 16.0 mm |
| Product Net Height: | 62.0 mm |
| Product Net Depth / Length: | 47.6 mm |
| Product Net Weight: | 0.027 kg |

Container Information

| | |
|--|---------------|
| Package Level 1 Units: | bag 10 piece |
| Package Level 1 Width: | 165 mm |
| Package Level 1 Depth / Length: | 70 mm |
| Package Level 1 Height: | 16 mm |
| Package Level 1 Gross Weight: | 0.032 kg |
| Package Level 1 EAN: | 6417019926216 |

Technical

| | |
|--|-------------------------------|
| Cable Cross-Section: | Cu 0.75...2.5 mm ² |
| Conventional Free-air Thermal Current (I_{th} 16 A): | |
| Conventional Thermal Current (I_{the}): | 16 A |
| Mounting Type: | Door mounting |
| Rated Insulation Voltage (U_i): | acc. to IEC 60947-1 690 V |
| Recommended Screw Driver: | Main Circuit Pozidriv 2 |

| | |
|-------------------------------|---|
| Terminal Type: | Screw Terminals |
| Tightening Torque: | acc. IEC 60947-1 0.8 N·m |
| Wire Stripping Length: | Main Circuit 8-10 mm Main Circuit 0.31-0.39 in |

Technical UL/CSA

| | |
|----------------------------------|-------------|
| Wire Size: | 18-14 AWG |
| Tightening Torque UL/CSA: | UL 7 lbf·in |

Certificates and Declarations

| | |
|--|-----------------|
| Declaration of Conformity - CE: | 1SCC390103D2701 |
|--|-----------------|

External Classifications and Standards

| | |
|--|--|
| Object Classification Code: | Q |
| ETIM 9: | EC000041 - Auxiliary contact block |
| ETIM 10: | EC000041 - Auxiliary contact block |
| UNSPSC: | 39121522 |
| IDEA Granular Category Code (IGCC): | 4743 >> Auxiliary contact block |
| eClass: | V11.1 : 27371302 |
| WEEE Category: | 5. Small Equipment (No External Dimension More Than 50 cm) |
| E-Number (Finland): | 3660439 |
| E-Number (Norway): | 4384791 |
| E-Number (Sweden): | 3172189 |

Categories

Products > Low Voltage Products and Systems > Switches > Switch Disconnectors



