

Specifications



Eaton FT3EW4IATL18IP

Eaton FlexiTech, Exit Wall, 30m, 4 picto.
(DRLU), AT L', 1 to 8H, IP66

General specifications

PRODUCT NAME	Eaton FlexiTech EW SC exit sign
CATALOG NUMBER	FT3EW4IATL18IP
EAN	3660191809201
PRODUCT LENGTH/DEPTH	326 mm
PRODUCT HEIGHT	38 mm
PRODUCT WIDTH	178 mm
PRODUCT WEIGHT	0.853 kg
CERTIFICATIONS	CE

Application

APPLICATION	Acc. EN 1838
MOUNTING METHOD	Wall surface mounted
OUTDOOR USE COMPLIANCE	False
TYPE OF INDICATOR	Only single-sided

General information

FUNCTION	Escape route signage
KIND OF LUMINAIRE	Exit sign luminaire
LABELLING TYPE	Insert sheet/plate
LIGHT DISTRIBUTOR	Diffuser lens/optic/panel
LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN D	No
MODE	Maintained / Non-Maintained (M / NM)
PICTOGRAM INCLUDED	Yes
WITH REMOTE SWITCH CONNECTION	No

Light source specifications

COLOR OF LIGHT	White
COLOR RENDERING INDEX (CRI)	80
ENERGY EFFICIENCY CLASS	A
ENERGY EFFICIENCY CLASS OF THE BUILT-IN LAMP	A++, A+, A (LED)
LAMP HOLDER	None
LAMP TYPE	LED not exchangeable
RESERVE-POLARITY PROTECTED	True
SHAPE	Rectangular
WITH LIGHT SOURCE	Yes

Electrical specifications

BATTERY QUALITY	Lithium-ion
CONNECTION TYPE	Plug-in connection
EXPLOSION PROTECTED	False
POWER SUPPLY SYSTEM	Peripheral (individual battery)
PROTECTION CLASS	II
TYPE OF CONTROL GEAR	LED operating device current-controlled
TYPE OF WIRING	Suitable for through wiring
VOLTAGE TYPE	AC
WIRING SYSTEM	Continuous circuit/emergency circuit

Housing specifications

COLOR HOUSING	White
DEGREE OF PROTECTION	IP66
IMPACT STRENGTH	IK07
MATERIAL COVER	Plastic, transparent
MATERIAL HOUSING	Plastic
SHAPE	Rectangular

Miscellaneous specifications

FUNCTION	Escape route signage
KIND OF LUMINAIRE	Exit sign luminaire
LABELLING TYPE	Insert sheet/plate
LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN D	No
MODE	Maintained / Non-Maintained (M / NM)
PICTOGRAM INCLUDED	Yes
WITH REMOTE SWITCH CONNECTION	No

Monitoring options

MONITORING EQUIPMENT	Automatic self test
-----------------------------	---------------------

Testing systems

TESTING SYSTEM	Auto-Test
-----------------------	-----------

Product specifications

BATTERY QUALITY	Lithium-ion
COLOR HOUSING	White
DEGREE OF PROTECTION	IP66
LIGHT DISTRIBUTOR	Diffuser lens/optic/panel
PROTECTION CLASS	II
VOLTAGE TYPE	AC

Resources

CERTIFICATION REPORTS	eaton-emergency-lighting-self-contained-exit-safety-flexitech-ew-su-certificate-doc-en-fr-de
MANUALS AND USER GUIDES	eaton-emergency-lighting-self-contained-exit-flexitech-ew-20-30-atl-manual-all-lang.pdf
TECHNICAL DATA SHEETS	eaton-emergency-lighting-self-contained-exit-flexitech-ew-atl-datasheet-en.pdf

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

