

Specifications



Photo is representative

Eaton FT2EC4IATL18IP

Eaton FlexiTech, Exit Ceiling, 20m, 4 picto. (DRLU), AT L', 1 to 8H, IP65

General specifications

PRODUCT NAME	Eaton FlexiTech EC SC exit sign
CATALOG NUMBER	FT2EC4IATL18IP
EAN	3660191813628
PRODUCT LENGTH/DEPTH	229 mm
PRODUCT HEIGHT	50 mm
PRODUCT WIDTH	147 mm
PRODUCT WEIGHT	0.62 kg
CERTIFICATIONS	CE
GLOBAL CATALOG	FT2EC4IATL18IP
PRODUCT TYPE	Ceiling mounted exit sign

Product specifications

BATTERY VOLTAGE	3.2 V
BATTERY NUMBER OF CELLS	1
BATTERY QUALITY	Lithium-ion
GLOW WIRE TEST	850 °C
PERMISSIBLE AMBIENT TEMPERATURE - MIN	0 °C
PERMISSIBLE AMBIENT TEMPERATURE - MAX	45 °C
PROTECTION CLASS	II
OUTDOOR USE COMPLIANCE	False
EXPLOSION PROTECTED	False
DEGREE OF PROTECTION	IP65
MODE	Maintained / Non-Maintained (M / NM)
LAMP TYPE	LED not exchangeable
WITH LIGHT SOURCE	Yes
LAMP HOLDER	None
TYPE OF INDICATOR	Single/double-sided
MONITORING EQUIPMENT	Automatic self test
POWER SUPPLY SYSTEM	Peripheral (individual battery)
VOLTAGE TYPE	AC
APPARENT POWER AT MAINS OPERATION	5.3 VA
POWER FACTOR	0.47
WIRING SYSTEM	Continuous circuit/emergency circuit
WITH REMOTE SWITCH CONNECTION	No
RESERVE-POLARITY PROTECTED	True
ENERGY EFFICIENCY CLASS	A
CONDUCTOR CROSS SECTION	2.5
CONNECTION TYPE	Plug-in connection
MAX. SYSTEM POWER	2.5 W
RATED LIFE TIME L70/B50 AT 25 °C	100000 hour
TYPE OF CONTROL GEAR	LED operating device current-controlled
TYPE OF WIRING	Suitable for through wiring

Resources

CATALOGS	Emergency Lighting (Central Battery Systems) - Global catalogue
----------	---

NOMINAL VOLTAGE AC - MAX	230 V
NOMINAL VOLTAGE AC - MIN	230 V
RATED AMBIENT TEMP ACC. IEC62722-2-1 - MIN	0 °C
RATED AMBIENT TEMP ACC. IEC62722-2-1 - MAX	45 °C
NOMINAL OPERATION TIME - MIN	1 hour
NOMINAL OPERATION TIME - MAX	8 hour
AUTONOMY	1/8 hours
SUITABLE FOR STANDBY SWITCHING	No
SUITABLE FOR CONTINUOUS CIRCUIT	No
RAL-NUMBER (SIMILAR) HOUSING	9003
MOUNTING METHOD	Ceiling surface mounting
MATERIAL HOUSING	Plastic
COLOR HOUSING	White
MATERIAL COVER	Plastic, transparent
LABELLING TYPE	Insert sheet/plate
PICTOGRAM INCLUDED	Yes
NUMBER OF POLES (NUMERIC)	3
IMPACT STRENGTH	IK07
KIND OF LUMINAIRE	Exit sign luminaire
COLOR TEMPERATURE - MAX	6500 K
COLOR TEMPERATURE - MIN	6500 K
LIGHT DISTRIBUTOR	Diffuser lens/optic/panel
ENERGY EFFICIENCY CLASS OF THE BUILT-IN LAMP	A++, A+, A (LED)
FUNCTION	Escape route signage
COLOR OF LIGHT	White
COLOR RENDERING INDEX (CRI)	80
LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN D	No
NUMBER OF LIGHTING HEADS	2
SUITABLE FOR NUMBER OF LAMPS	2

VIEWING DISTANCE	20 m
DATA CONNECTION TERMINAL	0.5-2.5 mm ²
FREQUENCY	50/60 Hz
MAIN CONNECTION TERMINAL	0.5 - 2.5mm ²
NUMBER OF LEDS	32
SHAPE	Rectangular
APPLICATION	Acc. EN 1838
TESTING SYSTEM	Auto-Test
WITH REMOTE CONTROL	No
CONSTANT LIGHT OUTPUT (CLO)	No
EXCHANGEABLE CONTROL GEAR	No
EMERGENCY FUNCTION MONITORING SYSTEM	Automatic self test
EMERGENCY POWER SUPPLY SYSTEM	Peripheral (individual battery)
POWER CONSUMPTION IN EMERGENCY MODE	2.5 W
TYPE OF LITHIUM-ION BATTERY	Lithium iron phosphate (LiFePO ₄)
WITH HEATING ELEMENT FOR BATTERY	No
CONNECTABLE CONDUCTOR CROSS SECTION - MIN	0.5 mm ²
CONNECTABLE CONDUCTOR CROSS SECTION - MAX	2.5 mm ²

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
 30 Pembroke Road
 Dublin 4, Ireland
 Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

