

Specifications



Photo is representative

Eaton FT2SE600ATT13IP

Eaton FlexiTech, Safety Escape Route, 600lm, AT, MNM, Tel, 1 to 3H, IP65

General specifications

PRODUCT NAME	Eaton FlexiTech SE SC emergency luminaire
CATALOG NUMBER	FT2SE600ATT13IP
EAN	3660191806965
PRODUCT LENGTH/DEPTH	228 mm
PRODUCT HEIGHT	31 mm
PRODUCT WIDTH	120 mm
PRODUCT WEIGHT	0.4 kg
CERTIFICATIONS	CE



Powering Business Worldwide

Application

APPLICATION	Other
MOUNTING METHOD	Ceiling surface mounting
OUTDOOR USE COMPLIANCE	False

General information

FUNCTION	Escape route lighting
KIND OF LUMINAIRE	Safety luminaire for escape route and open area lighting
LABELLING TYPE	Other
LIGHT DISTRIBUTOR	Focal lens
LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN D	No
MODE	Maintained / Non-Maintained (M / NM)
PICTOGRAM INCLUDED	No
WITH REMOTE SWITCH CONNECTION	Yes

Electrical specifications

BATTERY QUALITY	Lithium-ion
CONNECTION TYPE	Plug-in connection
EXPLOSION PROTECTED	False
POWER SUPPLY SYSTEM	Peripheral (individual battery)
PROTECTION CLASS	II
TYPE OF CONTROL GEAR	LED operating device current-controlled
TYPE OF WIRING	Suitable for through wiring
VOLTAGE TYPE	AC
WIRING SYSTEM	Continuous circuit/emergency circuit

Housing specifications

COLOR HOUSING	White
DEGREE OF PROTECTION	IP65
IMPACT STRENGTH	IK07
MATERIAL COVER	Plastic, transparent
MATERIAL HOUSING	Plastic
SHAPE	Rectangular

Light source specifications

COLOR OF LIGHT	White
COLOR RENDERING INDEX (CRI)	70
ENERGY EFFICIENCY CLASS	A
ENERGY EFFICIENCY CLASS OF THE BUILT-IN LAMP	A++, A+, A (LED)
LAMP HOLDER	None
LAMP TYPE	LED not exchangeable
RESERVE-POLARITY PROTECTED	True
SHAPE	Rectangular
WITH LIGHT SOURCE	Yes

Monitoring options

MONITORING EQUIPMENT	Automatic self test
-----------------------------	---------------------

Testing systems

TESTING SYSTEM	Auto-Test
-----------------------	-----------

Miscellaneous specifications

FUNCTION	Escape route lighting
KIND OF LUMINAIRE	Safety luminaire for escape route and open area lighting
LABELLING TYPE	Other
LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN D	No
MODE	Maintained / Non-Maintained (M / NM)
PICTOGRAM INCLUDED	No
WITH REMOTE SWITCH CONNECTION	Yes

Product specifications

BATTERY QUALITY	Lithium-ion
COLOR HOUSING	White
DEGREE OF PROTECTION	IP65
LIGHT DISTRIBUTOR	Focal lens
PROTECTION CLASS	II
VOLTAGE TYPE	AC

Resources

BROCHURES	eaton-emergency-lighting-self-contained-exit-safety-flexitech-ed-se-brochure-en.pdf
CATALOGUES	Emergency Lighting (Central Battery Systems) - Global catalogue
DECLARATIONS OF CONFORMITY	FlexiTech - Safety Instructions
MANUALS AND USER GUIDES	eaton-emergency-lighting-self-contained-safety-flexitech-se-att-manual-all-lang.pdf
TECHNICAL DATA SHEETS	eaton-emergency-lighting-self-contained-safety-flexitech-se-att-datasheet-en.pdf

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

