



Pendant/surface louvre fitting with narrow body

MODUS AREL 3500/3900/4400/5000lm, 1x LED, 1545mm, width 140mm, mat AL louvre, ceiling/pendant, LED 840, white RAL9016, 700/800/900/1050mA multi driver

Code: AREL5000XL1KVM4NDMULTI/9016

EAN: 8596099151386



## Luminaire properties

Product category:	Ceiling / wall luminaires	Effective luminous flux (lm):	3500,3900,4400,5000
System power (W):	29,33,38,44	Luminaire efficacy (lm/W):	114
Rated lifetime L70/B50 (h):	100000	Degree of protection (IP):	IP20
Color housing:	White	Suitable for suspended mounting:	Yes
Material housing:	Steel		
Light source included:	Yes		
Suitable for surface mounting:	Yes	Suitable for ceiling mounting:	Yes
Made in Czech republic:	Yes		

## Light source

Light source type:	LED	Color temperature (K):	4000
Color rendering index CRI:	80-89	Replaceability:	Removeable light source, replaceable ballast

## Optical system

Optical system:	KVM	Light outlet:	Direct
Type of grid:	Matt	Anti-glare limiting UGR:	19
Light sharing:	Symmetric	Fit for monitor workplace:	Yes

## Dimensions

Length (mm):	<b>1545</b>	Width (mm):	<b>140</b>
Height/depth (mm):	<b>65</b>	Weight (kg):	<b>4</b>

## Electrical values

Connection type:	<b>Pinching contact</b>	Voltage type:	<b>AC</b>
Type of control gear:	<b>LED operating device current-controlled</b>	Nominal voltage (V):	<b>220...240</b>
Control gear included:	<b>Yes</b>	Type of wiring:	<b>Suitable for through wiring</b>
No dim function:	<b>Yes</b>		