

SK 8 - Shield connection terminal block



3025163

<https://www.phoenixcontact.com/pc/products/3025163>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Shield connection clamp, for shield on busbars, contact resistance < 1 mΩ

Your advantages

- Easy handling
- Spring-loaded, large-surface pressure plate
- Suitable for direct and busbar mounting
- Knurled screw
- As components, it is not possible to certify shield connections in accordance with the requirements of the directive and standards for electrical equipment in potentially explosive areas. As such, shield connection clamps can be used in the Ex area even without an appropriate approval or marking.

Commercial data

Item number	3025163
Packing unit	10 pc
Minimum order quantity	10 pc
Product key	BE7512
GTIN	4017918130299
Weight per piece (including packing)	15.14 g
Weight per piece (excluding packing)	15.07 g
Customs tariff number	85369010
Country of origin	DE

SK 8 - Shield connection terminal block



3025163

<https://www.phoenixcontact.com/pc/products/3025163>

Technical data

Notes

General

Note	The shield connection clamps must not be used for strain relief of cables/conductors.
	Do not use for protective conductor connection.

Product properties

Product type	Shield connection clamp
Pitch	12 mm
Number of connections	1
Number of rows	1


Electrical properties

Maximum power dissipation for nominal condition	0 W
Contact resistance	< 0.001 Ω

Connection data

Grounding foot	Yes
Connection method	Screw connection
Screw thread	M4
Tightening torque	0.6 ... 0.6 Nm
Connection in acc. with standard	IEC / EN

Dimensions

Dimensional drawing	
Width	12 mm
Height	19.5 mm
Depth	48.7 mm
Pitch	12 mm

External dimensions

Outside diameter	3 mm ... 8 mm
------------------	---------------

Material specifications

Color	silver-colored
Material	Steel

Cable/line

SK 8 - Shield connection terminal block



3025163

<https://www.phoenixcontact.com/pc/products/3025163>

External cable diameter	3 mm ... 8 mm
-------------------------	---------------

Standards and regulations

Connection in acc. with standard	IEC / EN
----------------------------------	----------

Mounting

Mounting type	Neutral busbar
---------------	----------------

SK 8 - Shield connection terminal block


3025163

<https://www.phoenixcontact.com/pc/products/3025163>




Drawings


Dimensional drawing



Dimensional drawing



Diagram



SK 8 - Shield connection terminal block



3025163

<https://www.phoenixcontact.com/pc/products/3025163>

Classifications

ECLASS

ECLASS-13.0	27250309
ECLASS-15.0	27250309

ETIM

ETIM 10.0	EC002020
-----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

SK 8 - Shield connection terminal block



3025163

<https://www.phoenixcontact.com/pc/products/3025163>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

SK 8 - Shield connection terminal block

3025163

<https://www.phoenixcontact.com/pc/products/3025163>



Accessories

i Note: Applying some accessories below might limit this product.

NLS-CU 3/10 SN 1000MM - Neutral busbar

0402174

<https://www.phoenixcontact.com/pc/products/0402174>



Neutral busbar, DIN VDE 0611-4: 1991-02, color: silver-colored

i Max. current carrying capacity: 140 A

AK 4 - Connection terminal block

0404017

<https://www.phoenixcontact.com/pc/products/0404017>



Connection terminal block, connection method: Screw connection, Rated cross section: 4 mm², cross section: 0.5 mm² - 6 mm², mounting: Neutral busbar, color: silver

SK 8 - Shield connection terminal block

3025163

<https://www.phoenixcontact.com/pc/products/3025163>



AKG 4 GNYE - Connection terminal block

0421029

<https://www.phoenixcontact.com/pc/products/0421029>



Connection terminal block, nom. voltage: 300 V, nominal current: 41 A, connection method: Screw connection, Rated cross section: 4 mm², cross section: 0.5 mm² - 6 mm², mounting: Neutral busbar, color: green-yellow

AKG 4 BK - Connection terminal block

0421032

<https://www.phoenixcontact.com/pc/products/0421032>



Connection terminal block, nom. voltage: 300 V, nominal current: 41 A, connection method: Screw connection, Rated cross section: 4 mm², cross section: 0.5 mm² - 6 mm², mounting: Neutral busbar, color: black

SK 8 - Shield connection terminal block

3025163

<https://www.phoenixcontact.com/pc/products/3025163>



AB-SK TOP - Support bracket

3062090

<https://www.phoenixcontact.com/pc/products/3062090>



AB-SK TOP INSULATED - Support bracket

3062074

<https://www.phoenixcontact.com/pc/products/3062074>



SK 8 - Shield connection terminal block

3025163

<https://www.phoenixcontact.com/pc/products/3025163>



AB-SK - Support bracket

3025341

<https://www.phoenixcontact.com/pc/products/3025341>

Support bracket for busbars



AB-SK 65 - Support bracket

3026489

<https://www.phoenixcontact.com/pc/products/3026489>



SK 8 - Shield connection terminal block

3025163

<https://www.phoenixcontact.com/pc/products/3025163>



AB-SKS 60 - Support bracket

3240223

<https://www.phoenixcontact.com/pc/products/3240223>

Support bracket for busbars



AB-SK-D TOP - Support bracket

3062100

<https://www.phoenixcontact.com/pc/products/3062100>



SK 8 - Shield connection terminal block

3025163


<https://www.phoenixcontact.com/pc/products/3025163>



AB-SK-D TOP INSULATED - Support bracket

3062087

<https://www.phoenixcontact.com/pc/products/3062087>



AB-SK 65-D - Support bracket

3026900

<https://www.phoenixcontact.com/pc/products/3026900>



SK 8 - Shield connection terminal block

3025163

<https://www.phoenixcontact.com/pc/products/3025163>



AB-SK 65-D INSULATED - Support bracket

3040889

<https://www.phoenixcontact.com/pc/products/3040889>



AB/SS - Support bracket

0404428

<https://www.phoenixcontact.com/pc/products/0404428>



Support bracket made from insulation material, with retaining screw, can be used with either 3 x 10 mm or 6 x 6 mm busbar, color: gray

SK 8 - Shield connection terminal block

3025163

<https://www.phoenixcontact.com/pc/products/3025163>

AB/SS-M - Support bracket

3025888

<https://www.phoenixcontact.com/pc/products/3025888>



Support bracket, with contact to the mounting panel, with retaining screw, can be used for busbar 3 x 10 mm, color: gray

AB/SKS - Support bracket

3240224

<https://www.phoenixcontact.com/pc/products/3240224>



Support bracket for busbars

SK 8 - Shield connection terminal block

3025163

<https://www.phoenixcontact.com/pc/products/3025163>



AB-SK/E - Support bracket

3026476

<https://www.phoenixcontact.com/pc/products/3026476>



AB-SK/E-NS 35 - Support bracket

3213111

<https://www.phoenixcontact.com/pc/products/3213111>



SK 8 - Shield connection terminal block

3025163

<https://www.phoenixcontact.com/pc/products/3025163>



SZF 1-0,6X3,5 - Screwdriver

1204517

<https://www.phoenixcontact.com/pc/products/1204517>



Actuation tool, for ST terminal blocks, also suitable for use as a bladed screwdriver, size: 0.6 x 3.5 x 100 mm, 2-component grip, with non-slip grip

Phoenix Contact 2026 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG

Flachsmarktstraße 8

D-32825 Blomberg

+49 (0) 5235-3 00

info@phoenixcontact.com