

M23-12S2N1280DU - Cable connector



1543932

<https://www.phoenixcontact.com/pc/products/1543932>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



M23, Cable connector, application: Signal, series: M23 PRO, straight, shielded: yes, Screw locking mechanism, No. of pos.: 12, Direction of rotation: Counter direction, contact connection type: Socket, Solder connection, cable diameter range: 3 mm ... 15 mm, coding: N, Item is lead-free in accordance with RoHS II without Exemption 6c (Pb < 0.1 %)

The figure shows the product version with crimp contact insert. Insulating body differs in color

Your advantages

- Solutions with cross-manufacturer compatibility for standard and fast locking systems
- Modern, consistent design for highly convenient operation
- Easy, cost-effective cable assembly: uniform shielding of M17 to M40
- Reliable under the harshest conditions: cable connectors with vibration brake

Commercial data

Item number	1543932
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	ABRABA
GTIN	4067923016637
Weight per piece (including packing)	121.2 g
Weight per piece (excluding packing)	104.796 g
Customs tariff number	85366990
Country of origin	DE

M23-12S2N1280DU - Cable connector



1543932

<https://www.phoenixcontact.com/pc/products/1543932>

Technical data

Notes

Notes on operation	Please observe the derating curve.
Safety note	
Safety note	WARNING: The connectors may not be plugged in or disconnected under load. Ignoring the warning or improper use may damage persons and/or property. • WARNING: Commission properly functioning products only. The products must be regularly inspected for damage. Decommission defective products immediately. Replace damaged products. Repairs are not possible. • WARNING: Only electrically qualified personnel may install and operate the product. They must observe the following safety notes. The qualified personnel must be familiar with the basics of electrical engineering. They must be able to recognize and prevent danger. The relevant symbol on the packaging indicates that only personnel familiar with electrical engineering are allowed to install and operate the product. • The products are suitable for applications in plant, controller, and electrical device engineering. • When operating the connectors in outdoor applications, they must be separately protected against environmental influences. • Assembled products may not be manipulated or improperly opened. • Only use mating connectors that are specified in the technical data of the standards listed (e.g. the ones listed in the product accessories online at phoenixcontact.com/products). • When using the product in direct connection with third-party manufacturers, the user is responsible. • For operating voltages > 50 V AC, conductive connector housings must be grounded • Ensure that the protective or functional ground has been properly connected. • VDE 0100/1.97 § 411.1.3.2 and DIN EN 60 204/11.98 § 14.1.3 are applicable when combining several circuits in a cable and/or connector • Only use tools recommended by Phoenix Contact • The installation notes/Design In documents online on the download page at phoenixcontact.com/products must be observed for this product. • Operate the connector only when it is fully plugged in and interlocked. • Ensure that when laying the cable, the tensile load on the connectors does not exceed the upper limit specified in the standards. • Observe the minimum bending radius of the cable. Lay the cable without twisting it. • The connector warms up in normal operation. Depending on the ambient conditions, the surface of the connector can continue to warm up. In this case, the user is responsible for posting

M23-12S2N1280DU - Cable connector



1543932

<https://www.phoenixcontact.com/pc/products/1543932>

warnings (e.g. DIN EN ISO 13732-1:2008-12).

Product properties

Product type	Circular connector (cable-side)
Product family	M23 PRO

Connector

Connection 1

Head design	Socket
-------------	--------

Insulating body

Coding	N
Material (Insulating body)	PA 6.6
Material (Contact)	CuZn
Material (Contact surface)	Ni/Au
Flammability rating according to UL 94	V0
Connection method	Solder connection
Contact switching type	Socket
Application	Signal
Number of positions	12
Direction of rotation	Counter direction
Connection profile	12
Installation height	2000 m
Number (Signal contacts)	12
Contact diameter (Signal contacts)	1 mm
Litz wires Min. cross section (Signal contacts)	0.08 mm ²
Litz wires Max. cross section (Signal contacts)	1 mm ²
Rated current Contact (Signal contacts)	8 A (for max. connection cross section)
Rated voltage Contact (Signal contacts)	150 V
Rated surge voltage	2.5 kV
Overvoltage category	III
Degree of pollution	3

Housing

Type	Cable connector housing
Thread type	M23
Design	straight
Type of locking	Screw locking mechanism
Pg screw connection	none
Housing material	GD-Zn
Degree of protection (plugged in)	IP66/IP68 (2 m / 24 h) IP69K

Seal

External cable diameter	3 mm ... 15 mm (Universal gasket)
Seal material	FKM

M23-12S2N1280DU - Cable connector



1543932

<https://www.phoenixcontact.com/pc/products/1543932>

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-40 °C ... 105 °C (see to derating)
Altitude	2000 m
Permanent temperature	125 °C (DIN EN 60512-9-2 / 1000 h)


M23-12S2N1280DU - Cable connector

1543932

<https://www.phoenixcontact.com/pc/products/1543932>

Drawings

Dimensional drawing



Dimensional drawing, housing


M23-12S2N1280DU - Cable connector

1543932

<https://www.phoenixcontact.com/pc/products/1543932>



Schematic diagram




Contact chamber numbering (view of plug-in side), socket counter direction

M23-12S2N1280DU - Cable connector

1543932

<https://www.phoenixcontact.com/pc/products/1543932>



I = current strength, ϑ = ambient temperature, 12x 8 A

M23-12S2N1280DU - Cable connector



1543932

<https://www.phoenixcontact.com/pc/products/1543932>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/1543932>

 cUL Recognized Approval ID: E335019-20141210				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
keine				
	150 V	5 A	- 18	-

 UL Recognized Approval ID: E335019-20141210				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
keine				
	150 V	6 A	- 18	-

M23-12S2N1280DU - Cable connector



1543932

<https://www.phoenixcontact.com/pc/products/1543932>

Classifications

ECLASS

ECLASS-13.0	27440116
ECLASS-15.0	27440116

ETIM

ETIM 10.0	EC002635
-----------	----------

M23-12S2N1280DU - Cable connector



1543932

<https://www.phoenixcontact.com/pc/products/1543932>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

M23-12S2N1280DU - Cable connector



1543932

<https://www.phoenixcontact.com/pc/products/1543932>

Accessories

SF-Z0028 - Torque screwdriver

1607456

<https://www.phoenixcontact.com/pc/products/1607456>



Torque screwdriver for M23 knurl fastening, torque 2.5 Nm, can be used in the RC, UC, CA, SF, SH series

SF-Z0027 - Hook wrench

1607455

<https://www.phoenixcontact.com/pc/products/1607455>



Hook wrench for torque screwdrivers for M23 knurl fastening, can be used in the RC, UC, CA, SF, SH series

M23-12S2N1280DU - Cable connector

1543932

<https://www.phoenixcontact.com/pc/products/1543932>



RF-Z0007 - Special wrench

1614347

<https://www.phoenixcontact.com/pc/products/1614347>

Special wrench, series: RF



PROT-M23PRO-SG-IT-IP20 - Plastic protective cap

1055744

<https://www.phoenixcontact.com/pc/products/1055744>

Plastic protective cap, M23, series: M23 PRO Signal



M23-12S2N1280DU - Cable connector

1543932

<https://www.phoenixcontact.com/pc/products/1543932>



PROT-M23PRO-SG-IT-IP67 - Plastic protective cap

1055745

<https://www.phoenixcontact.com/pc/products/1055745>

Plastic protective cap, M23, series: M23 PRO Signal



Phoenix Contact 2026 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG

Flachsmarktstraße 8

D-32825 Blomberg

+49 (0) 5235-3 00

info@phoenixcontact.com