


Surface luminaire with IP54

MODUS KX 4600/5300/6000/7200lm, 1500mm, LED 840, opal cover, surface, 900-1050-1200-1400mA multi

Code: KX7000L4KO/NDMULTI

EAN: 8596099179212



Luminaire properties

Product category:	Ceiling / wall luminaires	Effective luminous flux (lm):	7200
System power (W):	47	Luminaire efficacy (lm/W):	153
Rated lifetime L70/B50 (h):	100000	Degree of protection (IP):	IP54
Color housing:	White	Suitable for suspended mounting:	Yes
Material housing:	Steel		
Light source included:	Yes		
Suitable for wall mounting:	Yes	Suitable for surface mounting:	Yes
Suitable for ceiling mounting:	Yes	Made in Czech republic:	Yes

Light source

Light source type:	LED	Color temperature (K):	4000
Color rendering index CRI:	80-89	Replaceability:	Replaceable light source by professional, replaceable ballast

Optical system

Optical system:	KO	Light outlet:	Direct
Light sharing:	Symmetric	Material cover:	Plastic, opal

Dimensions

Length (mm):	1500	Width (mm):	110
Height/depth (mm):	60	Weight (kg):	3

Electrical values

Connection type:	Pinching contact	Voltage type:	AC
Type of control gear:	LED operating device current-controlled	Nominal voltage (V):	220...240
Control gear included:	Yes	No dim function:	Yes