AI-TWIN SORTI BOX BU - Assortment box

3202986

https://www.phoenixcontact.com/pc/products/3202986

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Assortment box, supplied with TWIN ferrules in accordance with DIN 46228-4, 50 pcs. each AI-TWIN 2x0,5-8 WH, AI-TWIN 2x0,75-8 GY, AI-TWIN 2x1-8 RD, AI-TWIN 2x1,5-8 BK, 25 pcs. AI-TWIN 2x2,5-10 BU

Your advantages

- Color coding and the transparent cover facilitate fast access to the required ferrules
- The practical assortment boxes are designed to keep your workshop tidy
- Using the integrated euro-clip, they can be hung up on perforated board walls, for example, to save space

Commercial data

Item number	3202986
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	BH3416
GTIN	4017918947149
Weight per piece (including packing)	110.6 g
Weight per piece (excluding packing)	100.36 g
Customs tariff number	85369010
Country of origin	DE

Set consists of

AI-TWIN 2X 0,5 - 8 WH - Ferrule

3200933

https://www.phoenixcontact.com/pc/products/3200933



Ferrule, Length contact range: 8 mm, sleeve length: 15 mm, color: white

AI-TWIN 2X 0,75- 8 GY - Ferrule

3200807

https://www.phoenixcontact.com/pc/products/3200807



Ferrule, Length contact range: 8 mm, sleeve length: 15 mm, color: gray

AI-TWIN 2X 1 - 8 RD - Ferrule

3200810

https://www.phoenixcontact.com/pc/products/3200810



Ferrule, Length contact range: 8 mm, sleeve length: 15 mm, color: red

AI-TWIN 2X 1,5 - 8 BK - Ferrule

3200823

https://www.phoenixcontact.com/pc/products/3200823



Ferrule, Length contact range: 8 mm, sleeve length: 16 mm, color: black

AI-TWIN 2X 2,5 -10 BU - Ferrule

3200836

https://www.phoenixcontact.com/pc/products/3200836



Ferrule, Length contact range: 10 mm, sleeve length: 18.5 mm, color: blue

Technical data

Product properties

Product type	Assortment box

Material specifications

Color	blue (RAL 5015)
Material	CU-DHP
Flammability rating according to UL 94	HB
Coating	galvanically tin-plated
Components	free from silicone and halogen

Classifications

ECLASS

ECLASS-13.0	27400218
ECLASS-15.0	27400218

ETIM

ETIM 10.0	EC000524

UNSPSC

UNSPSC 21.0	39121400

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%

EF3.1 Climate Change

CO2e kg	1.562 kg CO2e

Accessories

CRIMPFOX CENTRUS 6S - Crimping pliers

1213144

https://www.phoenixcontact.com/pc/products/1213144



Crimping pliers, for uninsulated and insulated ferrules, DIN 46228 Part 1 and 4, from 0.14 mm^2 … 6 mm^2, also for TWIN ferrules up to 2 x 4 mm^2, automatic cross section adjustment, lateral insertion, equipped with fall protection

CRIMPFOX CENTRUS 6H - Crimping pliers

1213146

https://www.phoenixcontact.com/pc/products/1213146



Crimping pliers, for uninsulated and insulated ferrules, DIN 46228 Part 1 and 4, from 0.14 mm^2 … 6 mm^2, also for TWIN ferrules up to 2 x 4 mm^2, automatic cross section adjustment, lateral insertion, equipped with fall protection

CRIMPFOX CENTRUS 10S - Crimping pliers

1213154

https://www.phoenixcontact.com/pc/products/1213154



Crimping pliers, for uninsulated and insulated ferrules, DIN 46228 Part 1 and 4, from 0.14 mm^2 ... 10 mm^2, also for TWIN ferrules up to 2 x 4 mm^2, automatic cross section adjustment, lateral insertion, equipped with fall protection

CRIMPFOX CENTRUS 10H - Crimping pliers

1213156

https://www.phoenixcontact.com/pc/products/1213156



Crimping pliers, for uninsulated and insulated ferrules, DIN 46228 Part 1 and 4, from 0.14 mm^2 ... 10 mm^2, also for TWIN ferrules up to 2 x 4 mm^2, automatic cross section adjustment, lateral insertion, equipped with fall protection

CRIMPFOX DUO 10 - Crimping pliers

1031721

https://www.phoenixcontact.com/pc/products/1031721



Crimping pliers, contact connection type: Insulated and uninsulated ferrules, standards/specifications: DIN 46228-1, DIN 46228-4, UL 486F, form A, E, F, min. cross section: 0.14 mm^2, max. cross section: 10 mm^2, for TWIN ferrules up to 2 x 4 mm^2, automatic cross section adjustment, rotating die, lateral and frontal insertion, compression: Trapezoidal crimp, weight 305 g, black/green

CRIMPFOX 10T-F - Crimping pliers

1134913

https://www.phoenixcontact.com/pc/products/1134913



Crimping pliers, contact connection type: Insulated and uninsulated ferrules, standards/specifications: DIN 46228-1, DIN 46228-4, min. cross section: 0.14 mm^2, max. cross section: 10 mm^2, For TWIN ferrules up to 2 x 4 mm^2, automatic cross section adjustment, frontal insertion, compression: Trapezoidal crimp, weight 302 g, black

CRIMPFOX DUO 16S - Crimping pliers

1202877

https://www.phoenixcontact.com/pc/products/1202877



Crimping pliers, contact type: insulated and uninsulated ferrules, standards/regulations: DIN 46228-1, DIN 46228-4, UL 486F, Form A, E, F, cross-section, minimum: 0.14 mm^2, cross-section, maximum: 16 mm^2, for TWIN ferrules up to 2 mm^2 x 6 mm^2, automatic cross-section adjustment, rotating dies, lateral and front entry, crimping: square

CRIMPFOX CENTRUS 6S - Crimping pliers

1213144

https://www.phoenixcontact.com/pc/products/1213144



Crimping pliers, for uninsulated and insulated ferrules, DIN 46228 Part 1 and 4, from 0.14 mm^2 … 6 mm^2, also for TWIN ferrules up to 2 x 4 mm^2, automatic cross section adjustment, lateral insertion, equipped with fall protection

CRIMPFOX CENTRUS 6H - Crimping pliers

1213146

https://www.phoenixcontact.com/pc/products/1213146



Crimping pliers, for uninsulated and insulated ferrules, DIN 46228 Part 1 and 4, from 0.14 mm^2 ... 6 mm^2, also for TWIN ferrules up to 2 x 4 mm^2, automatic cross section adjustment, lateral insertion, equipped with fall protection

CRIMPFOX CENTRUS 10S - Crimping pliers

1213154

https://www.phoenixcontact.com/pc/products/1213154



Crimping pliers, for uninsulated and insulated ferrules, DIN 46228 Part 1 and 4, from 0.14 mm^2 ... 10 mm^2, also for TWIN ferrules up to 2 x 4 mm^2, automatic cross section adjustment, lateral insertion, equipped with fall protection

CRIMPFOX CENTRUS 10H - Crimping pliers

1213156

https://www.phoenixcontact.com/pc/products/1213156



Crimping pliers, for uninsulated and insulated ferrules, DIN 46228 Part 1 and 4, from 0.14 mm^2 ... 10 mm^2, also for TWIN ferrules up to 2 x 4 mm^2, automatic cross section adjustment, lateral insertion, equipped with fall protection

CRIMPFOX DUO 10 - Crimping pliers

1031721

https://www.phoenixcontact.com/pc/products/1031721



Crimping pliers, contact connection type: Insulated and uninsulated ferrules, standards/specifications: DIN 46228-1, DIN 46228-4, UL 486F, form A, E, F, min. cross section: 0.14 mm^2, max. cross section: 10 mm^2, for TWIN ferrules up to 2 x 4 mm^2, automatic cross section adjustment, rotating die, lateral and frontal insertion, compression: Trapezoidal crimp, weight 305 g, black/green

AI-TWIN SORTI BOX BU - Assortment box

3202986

https://www.phoenixcontact.com/pc/products/3202986

CRIMPFOX 10T-F - Crimping pliers

1134913

https://www.phoenixcontact.com/pc/products/1134913



Crimping pliers, contact connection type: Insulated and uninsulated ferrules, standards/specifications: DIN 46228-1, DIN 46228-4, min. cross section: 0.14 mm^2, max. cross section: 10 mm^2, For TWIN ferrules up to 2 x 4 mm^2, automatic cross section adjustment, frontal insertion, compression: Trapezoidal crimp, weight 302 g, black

CRIMPFOX DUO 16S - Crimping pliers

1202877

https://www.phoenixcontact.com/pc/products/1202877



Crimping pliers, contact type: insulated and uninsulated ferrules, standards/regulations: DIN 46228-1, DIN 46228-4, UL 486F, Form A, E, F, cross-section, minimum: 0.14 mm^2, cross-section, maximum: 16 mm^2, for TWIN ferrules up to 2 mm^2 x 6 mm^2, automatic cross-section adjustment, rotating dies, lateral and front entry, crimping: square

Phoenix Contact 2026 © - all rights reserved
https://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com