RIF-1-BPT/2X21 - Relay base

2900931

https://www.phoenixcontact.com/pc/products/2900931

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Relay base RIF-1..., for miniature power relay with 1 or 2 changeover contacts or solid-state relays of the same design, Push-in connection, plug-in option for input/interference suppression modules, for mounting on NS 35/7,5

Commercial data

Item number	2900931
Packing unit	10 pc
Minimum order quantity	10 pc
Product key	DK6522
GTIN	4046356733151
Weight per piece (including packing)	50.1 g
Weight per piece (excluding packing)	49.7 g
Customs tariff number	85366990
Country of origin	CN

Technical data

Notes

Notes on operation	FBS 2-6... plug-in bridge for the input side (A2) and FBS-2-8... plug-in bridge for the output side (11/21)

Product properties

Product type	Relay socket
Product family	RIFLINE complete
Set comprises	2903327 RIF-1-RPT-LV-230AC/2X21AU
	2903328 RIF-1-RPT-LV-120AC/2X21AU
	2903329 RIF-1-RPT-LV-24AC/2X21AU
	2903330 RIF-1-RPT-LDP-24DC/2X21AU
	2903331 RIF-1-RPT-LV-230AC/2X21
	2903332 RIF-1-RPT-LV-120AC/2X21
	2903333 RIF-1-RPT-LV-24AC/2X21
	2903334 RIF-1-RPT-LDP-24DC/2X21
	2903339 RIF-1-RPT-LV-230AC/1X21
	2903340 RIF-1-RPT-LV-120AC/1X21
	2903341 RIF-1-RPT-LV-24AC/1X21
	2903342 RIF-1-RPT-LDP-24DC/1X21
	2905289 RIF-1-RPT-LDP-24DC/1X21MS
	2905290 RIF-1-RPT-LV-230AC/1X21MS
	2905291 RIF-1-RPT-LDP-24DC/2X21MS
	2905292 RIF-1-RPT-LV-230AC/2X21MS
	2906223 RIF-1-RPT-LDP-12DC/2X21
	2906224 RIF-1-RPT-LDP-12DC/1X21
	2909775 RIF-1-RPT-LV-120AC/2X21MS
	2909776 RIF-1-RPT-LV-120AC/1X21MS
	2909884 RIF-1-RPT-LDP-24DC/1IC
	1049232 RIF-1-RPT-LV-24AC/2X21MS
	1078686 RIF-1-RPT-LDP-24DC/1ICT
	1188144 RIF-1-RPT-L-24AC/2X21MS
	1188142 RIF-1-RPT-LRC-230AC/2X21MS

Electrical properties

Nominal voltage U_N	250 V AC/DC
Nominal current I_N	max. 13 A (Depends on application/assembly)
Protective circuit	depending on the selected input/suppressor modules

Connection data

Connection method	Push-in connection
Stripping length	8 mm
Conductor cross-section rigid	0.14 mm² ... 1.5 mm²

Conductor cross-section flexible	0.14 mm² ... 1.5 mm²
	0.14 mm² ... 1.5 mm² (Ferrule with plastic sleeve)
	0.14 mm² ... 1 mm² (Ferrule with plastic sleeve, two conductors on double terminal block)
Conductor cross-section AWG	26 ... 16 (solid)
	26 ... 16 (flexible)

Dimensions

Item dimensions

Width	16 mm
Height	96 mm
Depth (Retaining bracket)	75 mm (with retaining bracket)

Drill hole

Diameter	3.2 mm

Material specifications

Color	gray (RAL 7042)
Flammability rating according to UL 94 (Housing)	V2 (Housing)

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-40 °C ... 85 °C (Depends on application/assembly)
Ambient temperature (storage/transport)	-40 °C ... 85 °C

Approvals

Corrosive gas test

Identification	ISA-S71.04. G3 Harsh Group
	EN 60068-2-60

Mounting

Mounting type	DIN rail mounting
Mounting position	any

Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/pc/products/2900931

CSA
Approval ID: 76787

UL Recognized
Approval ID: FILE E 113228

EAC
Approval ID: RU D-DE.B*00573/18

DNV
Approval ID: TAA000018V

Classifications

ECLASS

ECLASS-13.0	27371603
ECLASS-15.0	27371603

ETIM

ETIM 10.0	EC001456

UNSPSC

UNSPSC 21.0	39122300

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Mandatory accessories

REL-MR- 12DC/21HC - Single relay

2961309

https://www.phoenixcontact.com/pc/products/2961309




Plug-in miniature power relay, with power contact for high continuous currents, 1 changeover contact, input voltage 12 V DC

REL-MR- 24DC/21HC - Single relay

2961312

https://www.phoenixcontact.com/pc/products/2961312




Plug-in miniature power relay, with power contact for high continuous currents, 1 changeover contact, input voltage 24 V DC

REL-MR- 48DC/21HC - Single relay

2834821

https://www.phoenixcontact.com/pc/products/2834821




Plug-in miniature power relay, with power contact for high continuous currents, 1 changeover contact, input voltage 48 V DC

REL-MR- 60DC/21HC - Single relay

2961325

https://www.phoenixcontact.com/pc/products/2961325




Plug-in miniature power relay, with power contact for high continuous currents, 1 changeover contact, 60 V DC

REL-MR-110DC/21HC - Single relay

2961338

https://www.phoenixcontact.com/pc/products/2961338




Plug-in miniature power relay, with power contact for high continuous currents, 1 changeover contact, input voltage 110 V DC

REL-MR- 24AC/21HC - Single relay

2961406

https://www.phoenixcontact.com/pc/products/2961406




Plug-in miniature power relay, with power contact for high continuous currents, 1 changeover contact, input voltage 24 V AC

REL-MR-120AC/21HC - Single relay

2961419

https://www.phoenixcontact.com/pc/products/2961419




Plug-in miniature power relay, with power contact for high continuous currents, 1 changeover contact, input voltage 120 V AC

REL-MR-230AC/21HC - Single relay

2961422

https://www.phoenixcontact.com/pc/products/2961422




Plug-in miniature power relay, with power contact for high continuous currents, 1 changeover contact, input voltage 230 V AC

REL-MR- 24DC/21HC AU - Single relay

2961545

https://www.phoenixcontact.com/pc/products/2961545



Plug-in miniature power relay, with multi-layer gold contact for high continuous currents, 1 changeover contact, input voltage 24 V DC

REL-MR-110DC/21HC AU - Single relay

2961561

https://www.phoenixcontact.com/pc/products/2961561




Plug-in miniature power relay, with multi-layer gold contact for high continuous currents, 1 changeover contact, input voltage 110 V DC

REL-MR- 24AC/21HC AU - Single relay

2961503

https://www.phoenixcontact.com/pc/products/2961503




Plug-in miniature power relay, with multi-layer gold contact for high continuous currents, 1 changeover contact, input voltage 24 V AC

REL-MR-120AC/21HC AU - Single relay

2961516

https://www.phoenixcontact.com/pc/products/2961516




Plug-in miniature power relay, with multi-layer gold contact for high continuous currents, 1 changeover contact, input voltage 120 V AC

REL-MR-230AC/21HC AU - Single relay

2961529

https://www.phoenixcontact.com/pc/products/2961529



Plug-in miniature power relay, with multi-layer gold contact for high continuous currents, 1 changeover contact, input voltage 230 V AC

REL-MR- 12DC/21-21 - Single relay

2961257

https://www.phoenixcontact.com/pc/products/2961257




Plug-in miniature power relay, with power contact, 2 changeover contacts, input voltage 12 V DC

REL-MR- 24DC/21-21 - Single relay

2961192

https://www.phoenixcontact.com/pc/products/2961192




Plug-in miniature power relay, with power contact, 2 changeover contacts, input voltage 24 V DC

REL-MR- 48DC/21-21 - Single relay

2834834

https://www.phoenixcontact.com/pc/products/2834834




Plug-in miniature power relay, with power contact, 2 changeover contacts, input voltage 48 V DC

REL-MR- 60DC/21-21 - Single relay

2961273

https://www.phoenixcontact.com/pc/products/2961273



Plug-in miniature power relay, with power contact, 2 changeover contacts, input voltage 60 V DC

REL-MR-110DC/21-21 - Single relay

2961202

https://www.phoenixcontact.com/pc/products/2961202




Plug-in miniature power relay, with power contact, 2 changeover contacts, input voltage 110 V DC

REL-MR- 24AC/21-21 - Single relay

2961435

https://www.phoenixcontact.com/pc/products/2961435




Plug-in miniature power relay, with power contact, 2 changeover contacts, input voltage 24 V AC

REL-MR-120AC/21-21 - Single relay

2961448

https://www.phoenixcontact.com/pc/products/2961448




Plug-in miniature power relay, with power contact, 2 changeover contacts, input voltage 120 V AC

REL-MR-230AC/21-21 - Single relay

2961451

https://www.phoenixcontact.com/pc/products/2961451



Plug-in miniature power relay, with power contact, 2 changeover contacts, input voltage 230 V AC

REL-MR- 12DC/21-21AU - Single relay

2961299

https://www.phoenixcontact.com/pc/products/2961299




Plug-in miniature power relay, with multi-layer gold contact, 2 changeover contacts, input voltage 12 V DC

REL-MR- 24DC/21-21AU - Single relay

2961215

https://www.phoenixcontact.com/pc/products/2961215



Plug-in miniature power relay, with multi-layer gold contact, 2 changeover contacts, input voltage 24 V DC

REL-MR- 48DC/21-21AU - Single relay

2834847

https://www.phoenixcontact.com/pc/products/2834847




Plug-in miniature power relay, with multi-layer gold contact, 2 changeover contacts, input voltage 48 V DC

REL-MR- 60DC/21-21AU - Single relay

2961286

https://www.phoenixcontact.com/pc/products/2961286



Plug-in miniature power relay, with multi-layer gold contact, 2 changeover contacts, input voltage 60 V DC

REL-MR-110DC/21-21AU - Single relay

2961228

https://www.phoenixcontact.com/pc/products/2961228




Plug-in miniature power relay, with multi-layer gold contact, 2 changeover contacts, input voltage 110 V DC

REL-MR- 24AC/21-21AU - Single relay

2961464

https://www.phoenixcontact.com/pc/products/2961464



Plug-in miniature power relay, with multi-layer gold contact, 2 changeover contacts, input voltage 24 V AC

REL-MR-120AC/21-21AU - Single relay

2961477

https://www.phoenixcontact.com/pc/products/2961477




Plug-in miniature power relay, with multi-layer gold contact, 2 changeover contacts, input voltage 120 V AC

REL-MR-230AC/21-21AU - Single relay

2961480

https://www.phoenixcontact.com/pc/products/2961480



Plug-in miniature power relay, with multi-layer gold contact, 2 changeover contacts, input voltage 230 V AC

REL-MR- 24DC/21HC/MS - Single relay

2987888

https://www.phoenixcontact.com/pc/products/2987888



Plug-in miniature relay, with power contact, 1 changeover contact, test button, mechanical switching position indicator, status LED, freewheeling diode, polarity A1+, A2-, input voltage 24 V DC

REL-MR- 24AC/21HC/MS - Single relay

2987891

https://www.phoenixcontact.com/pc/products/2987891



Plug-in miniature relay, with power contact, 1 changeover contact, test button, mechanical switching position indicator, status LED, input voltage 24 V AC

REL-MR-120AC/21HC/MS - Single relay

2987901

https://www.phoenixcontact.com/pc/products/2987901



Plug-in miniature relay, with power contact, 1 changeover contact, test button, mechanical switching position indicator, status LED, input voltage 120 V AC

REL-MR-230AC/21HC/MS - Single relay

2987914

https://www.phoenixcontact.com/pc/products/2987914



Plug-in miniature relay, with power contact, 1 changeover contact, test button, mechanical switching position indicator, status LED, input voltage 230 V AC

REL-MR- 24DC/21HC AU/MS - Single relay

2987927

https://www.phoenixcontact.com/pc/products/2987927



Plug-in miniature relay, with multi-layer contact with hard gold coating, 1 changeover contact, test button, mechanical switching position indicator, status LED, freewheeling diode, polarity A1+, A2-, input voltage 24 V DC

REL-MR-230AC/21HC AU/MS - Single relay

2987930

https://www.phoenixcontact.com/pc/products/2987930



Plug-in miniature relay, with multi-layer contact with hard gold coating, 1 changeover contact, test button, mechanical switching position indicator, status LED, input voltage 230 V AC

REL-MR- 24DC/21-21/MS - Single relay

2987943

https://www.phoenixcontact.com/pc/products/2987943



Plug-in miniature relay, with power contact, 2 changeover contacts, test button, mechanical switching position indicator, status LED, freewheeling diode, polarity A1+, A2, input voltage 24 V DC

REL-MR- 24AC/21-21/MS - Single relay

2987956

https://www.phoenixcontact.com/pc/products/2987956



Plug-in miniature relay, with power contact, 2 changeover contacts, test button, mechanical switching position indicator, status LED, input voltage 24 V AC

REL-MR-120AC/21-21/MS - Single relay

2987969

https://www.phoenixcontact.com/pc/products/2987969



Plug-in miniature relay, with power contact, 2 changeover contacts, test button, mechanical switching position indicator, status LED, coil voltage 120 V AC

REL-MR-230AC/21-21/MS - Single relay

2987972

https://www.phoenixcontact.com/pc/products/2987972



Plug-in miniature relay, with power contact, 2 changeover contacts, test button, mechanical switching position indicator, status LED, coil voltage 230 V AC

REL-MR- 24DC/21-21AU/MS - Single relay

2987985

https://www.phoenixcontact.com/pc/products/2987985



Plug-in miniature relay, with multi-layer contact with hard gold coating, 2 changeover contacts, test button, mechanical switching position indicator, status LED, freewheeling diode, polarity A1+, A2-, input voltage 24 V DC

REL-MR-230AC/21-21AU/MS - Single relay

2987998

https://www.phoenixcontact.com/pc/products/2987998



Plug-in miniature relay, with multi-layer contact with hard gold coating, 2 changeover contacts, test button, mechanical switching position indicator, status LED, coil voltage 230 V AC

OPT- 5DC/ 24DC/ 5 - Miniature solid-state relay

2982113

https://www.phoenixcontact.com/pc/products/2982113



Plug-in miniature solid-state relay, power solid-state relay, 1 N/O contact, input: 5 V DC, output: 3 - 33 V DC/5 A

OPT-24DC/ 24DC/ 5 - Miniature solid-state relay

2982100

https://www.phoenixcontact.com/pc/products/2982100



Plug-in miniature solid-state relay, power solid-state relay, 1 N/O contact, input: 24 V DC, output: 3 - 33 V DC/5 A

OPT-60DC/ 24DC/ 5 - Miniature solid-state relay

2982126

https://www.phoenixcontact.com/pc/products/2982126



Plug-in miniature solid-state relay, power solid-state relay, 1 N/O contact, input: 60 V DC, output: 3 - 33 V DC/5 A

OPT- 5DC/230AC/ 2 - Miniature solid-state relay

2982168

https://www.phoenixcontact.com/pc/products/2982168



Plug-in miniature solid-state relay, power solid-state relay, 1 N/O contact, input: 5 V DC, output: 24 - 253 V AC/2 A

OPT-24DC/230AC/ 2 - Miniature solid-state relay

2982171

https://www.phoenixcontact.com/pc/products/2982171



Plug-in miniature solid-state relay, power solid-state relay, 1 N/O contact, input: 24 V DC, output: 24 - 253 V AC/2 A

Accessories

FBS 2-6 - Plug-in bridge

3030336

https://www.phoenixcontact.com/pc/products/3030336



Plug-in bridge, pitch: 6.2 mm, number of positions: 2, nominal current: 32 A, color: red

FBS 2-6 BU - Plug-in bridge

3036932

https://www.phoenixcontact.com/pc/products/3036932



Plug-in bridge, pitch: 6.2 mm, number of positions: 2, nominal current: 32 A, color: blue

FBS 2-6 GY - Plug-in bridge

3032237

https://www.phoenixcontact.com/pc/products/3032237



Plug-in bridge, pitch: 6.2 mm, number of positions: 2, nominal current: 32 A, color: gray

FBS 2-8 - Plug-in bridge

3030284

https://www.phoenixcontact.com/pc/products/3030284



Plug-in bridge, pitch: 8.2 mm, number of positions: 2, nominal current: 41 A, color: red

FBS 2-8 BU - Plug-in bridge

3032567

https://www.phoenixcontact.com/pc/products/3032567



Plug-in bridge, pitch: 8.2 mm, number of positions: 2, nominal current: 41 A, color: blue

FBS 2-8 GY 7042 - Plug-in bridge

3032541

https://www.phoenixcontact.com/pc/products/3032541



Bridge for potential distribution

RIF-RH-1 - Retaining bracket

2900953

https://www.phoenixcontact.com/pc/products/2900953



Relay retaining bracket, with ejector function and holder for marking material, suitable for RIF-1 relay base, for 16 mm tall miniature power relay and solid-state relay

RIF-RH-1-H - Retaining bracket

2904468

https://www.phoenixcontact.com/pc/products/2904468



Relay retaining bracket, with ejector function and holder for marking material, suitable for RIF-1 relay base, for 25 mm tall miniature power relay and solid-state relay

RIF-RHM-1 - Relay retaining bracket

2905986

https://www.phoenixcontact.com/pc/products/2905986



Relay retaining bracket, wire model, suitable for RIF-1 relay base, for 16 mm high miniature power relays and solid-state relays

RIF-RHM-1-H - Relay retaining bracket

2905985

https://www.phoenixcontact.com/pc/products/2905985



Relay retaining bracket, wire model, suitable for RIF-1 relay base, for 25 mm high octal miniature power relays

STP 5-2 - Marker carriers

0800967

https://www.phoenixcontact.com/pc/products/0800967



Marker carriers, snaps into STTB 2,5, STTB 4, PTTB 2,5, and PTTB 4 double-level spring-cage terminal blocks, can be marked with UC-TM 5, UC-TMF 5, UCT-TM 5, UCT-TMF 5, ZB 5, or ZBF 5, gray (RAL 7042), unmarked, mounting type: plug in, text field height: 10.5 mm, text field width: 5 mm

MPS-MT - Test plug

0201744

https://www.phoenixcontact.com/pc/products/0201744



Test plug, with solder connection up to 1 mm^2 conductor cross-section, number of positions: 1, color: gray

RIF-1-V8/PT/FLK14/OUT - System connection

2905195

https://www.phoenixcontact.com/pc/products/2905195



V8 adapter for 8 x RIF-1 relay base, controller: PLC system cabling of output cards, connection 1: Push-in connection 4x, connection 2: IDC/FLK pin strip 1x 14-position, connection 3: Plug-in connection, number of channels: 8, control logic: positive switching

RIF-LDP-12-24 DC - Plug-in module

2900939

https://www.phoenixcontact.com/pc/products/2900939



Plug-in module, for mounting on RIF-1, RIF-2, RIF-3, and RIF-4, with freewheeling diode and yellow LED, polarity: A1+, A2-, input voltage: 12 V DC ... 24 V DC ±30 %

RIF-LDP-48-60 DC - Plug-in module

2900940

https://www.phoenixcontact.com/pc/products/2900940



Plug-in module, for mounting on RIF-1, RIF-2, RIF-3, and RIF-4, with freewheeling diode and yellow LED, polarity: A1+, A2-, input voltage: 48 V DC ... 60 V DC ±20 %

RIF-LDP-110 DC - Plug-in module

2900941

https://www.phoenixcontact.com/pc/products/2900941



Plug-in module, for mounting on RIF-1, RIF-2, RIF-3, and RIF-4, with freewheeling diode and yellow LED, polarity: A1+, A2-, input voltage: 110 V DC ±20 %

RIF-LV-12-24 UC - Plug-in module

2900942

https://www.phoenixcontact.com/pc/products/2900942



Plug-in module, for mounting on RIF-1, RIF-2, RIF-3, and RIF-4, with varistor and yellow LED, input voltage: 12 V AC ... 24 V AC / DC ±20 %

RIF-LV-48-60 UC - Plug-in module

2900943

https://www.phoenixcontact.com/pc/products/2900943



Plug-in module, for mounting on RIF-1, RIF-2, RIF-3, and RIF-4, with varistor and yellow LED, input voltage: 48 V AC ... 60 V AC / DC ±20 %

RIF-LV-120-230 AC/110 DC - Plug-in module

2900944

https://www.phoenixcontact.com/pc/products/2900944



Plug-in module, for mounting on RIF-1, RIF-2, RIF-3, and RIF-4, with varistor and yellow LED, input voltage: 120 V AC... 230 V AC / 110 V DC ±20 %

RIF-V-12-24 UC - Plug-in module

2900945

https://www.phoenixcontact.com/pc/products/2900945



Plug-in module, for mounting on RIF-1, RIF-2, RIF-3, and RIF-4, with varistor, input voltage: 12 V AC ... 24 V AC / DC ±20 %

RIF-V-120-230 UC - Plug-in module

2900948

https://www.phoenixcontact.com/pc/products/2900948



Plug-in module, for mounting on RIF-1, RIF-2, RIF-3, and RIF-4, with varistor, input voltage: 120 V AC ... 230 V AC / DC ±20 %

RIF-RC-12-24 UC - Plug-in module

2900949

https://www.phoenixcontact.com/pc/products/2900949



Plug-in module, for mounting on RIF-1, RIF-2, RIF-3, and RIF-4, with RC element, input voltage: 12 V AC ... 24 V AC / DC ±20 %

RIF-RC-120-230 UC - Plug-in module

2900951

https://www.phoenixcontact.com/pc/products/2900951



Plug-in module, for mounting on RIF-1, RIF-2, RIF-3, and RIF-4, with RC element, input voltage: 120 V AC ... 230 V AC / DC ±20 %

RIF-T3-24UC - Timer module

2902647

https://www.phoenixcontact.com/pc/products/2902647



Plug-in module for extending a relay module to create a timer relay, 3 time functions, 4 time ranges, for mounting on RIF-1, RIF-2, RIF-3, and RIF-4, input voltage: 12 V DC ... 24 V DC

RIF-BR-12-230 AC - Plug-in module

2907060

https://www.phoenixcontact.com/pc/products/2907060



Plug-in module, for mounting on RIF-1, RIF-2, RIF-3, and RIF-4, with bridge rectifier, input voltage: 12 V AC ... 230 V AC

RIF-LDM-12-24 DC - Plug-in module

2907057

https://www.phoenixcontact.com/pc/products/2907057



Plug-in module, for mounting on RIF-1, RIF-2, RIF-3, and RIF-4, with freewheeling diode and yellow LED, input voltage: 12 V DC ... 24 V DC ±20 %, polarity A1-, A2+

NS 35/ 7,5 PERF 2000MM - DIN rail perforated

0801733

https://www.phoenixcontact.com/pc/products/0801733



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

NS 35/ 7,5 UNPERF 2000MM - DIN rail, unperforated

0801681

https://www.phoenixcontact.com/pc/products/0801681



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver-colored

NS 35/ 7,5 WH PERF 2000MM - DIN rail perforated

1204119

https://www.phoenixcontact.com/pc/products/1204119



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, white passivated, Standard profile, color: silver-colored

NS 35/ 7,5 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204122

https://www.phoenixcontact.com/pc/products/1204122



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, white passivated, Standard profile, color: silver-colored

NS 35/ 7,5 AL UNPERF 2000MM - DIN rail, unperforated

0801704

https://www.phoenixcontact.com/pc/products/0801704



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver-colored

NS 35/ 7,5 ZN PERF 2000MM - DIN rail perforated

1206421

https://www.phoenixcontact.com/pc/products/1206421



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, zinc plating, Standard profile, color: silver-colored

NS 35/ 7,5 ZN UNPERF 2000MM - DIN rail, unperforated

1206434

https://www.phoenixcontact.com/pc/products/1206434



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, zinc plating, Standard profile, color: silver-colored

NS 35/ 7,5 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

0801762

https://www.phoenixcontact.com/pc/products/0801762



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored

NS 35/15 PERF 2000MM - DIN rail perforated

1201730

https://www.phoenixcontact.com/pc/products/1201730



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver-colored

NS 35/15 UNPERF 2000MM - DIN rail, unperforated

1201714

https://www.phoenixcontact.com/pc/products/1201714



DIN rail, unperforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver-colored

NS 35/15 WH PERF 2000MM - DIN rail perforated

0806602

https://www.phoenixcontact.com/pc/products/0806602



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, white passivated, Standard profile, color: white

NS 35/15 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204135

https://www.phoenixcontact.com/pc/products/1204135



DIN rail, unperforated, Pack of 10 (20 m), similar to EN 60715, material: Steel, galvanized, white passivated, Standard profile, color: silver-colored

NS 35/15 AL UNPERF 2000MM - DIN rail, unperforated

1201756

https://www.phoenixcontact.com/pc/products/1201756



DIN rail, unperforated, similar to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver-colored

NS 35/15 ZN PERF 2000MM - DIN rail perforated

1206599

https://www.phoenixcontact.com/pc/products/1206599



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, zinc plating, Standard profile, color: silver-colored

NS 35/15 ZN UNPERF 2000MM - DIN rail, unperforated

1206586

https://www.phoenixcontact.com/pc/products/1206586



DIN rail, unperforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, zinc plating, Standard profile, color: silver-colored

NS 35/15 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201895

https://www.phoenixcontact.com/pc/products/1201895



DIN rail, unperforated, Pack of 10 (20 m), similar to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored

RIF-1-BPT/2X21 - Relay base

2900931

https://www.phoenixcontact.com/pc/products/2900931

NS 35/15-2,3 UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201798

https://www.phoenixcontact.com/pc/products/1201798



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile 2.3 mm, color: silver-colored

Phoenix Contact 2026 © - all rights reserved
https://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com