PHILIPS

BVP169
LED157/830_40_65 PSU
135W AWB
911401885386



Multi ColorTemp

Ledinaire All-in floodlights, 135 W, 15000 lm, 15750 lm, 3000 K, 4000 K, 6500 K, CRI80, Asymmetrical, IP65

Aluminium die cast, Grey, Traffic grey B (RAL7043), Single layer powder coating, Power supply unit (On/Off), All-in, Multi Color Temperature, 15000 lm, 15750 lm, 135 W, 115 lm/W, 110 lm/W, 3000 K, 4000 K, 6500 K, (0.440,0.403); (0.369,0.364); (0.313,0.337) SDCM<5, CRI80, Asymmetrical, IP65 | Dust penetration-protected, jet-proof, IK08 | 5 J vandal-protected, Safety class I, Surge protection level until 1.5 kV differential mode and 1.5 kV common mode, Cable 2.0 m without plug, Flying leads/cables

General Information

Lamp family code	LED157-4S [LED module, system flux 15500 lm]
Number of gear units	Unit
Driver included	Yes
Sustainability rating	Unclassified
Light source engine type	LED system in flux
Service Tag	No
Value ladder	Value
Warranty period	5 years

Light Technical

Upwards light output ratio	0
Luminous Flux	15,000 lm
Correlated Colour Temperature (Nom)	3000 K
Luminous efficacy (rated) (nom.)	115 lm/W
Colour rendering index (CRI)	>80
Light source colour	Multi Colour Temperature
Optic type	Assymetric beam angle
Luminaire light beam spread	92° x 52°
Optic type outdoor	Asymmetrical
All-in Type	All-in, Multi Color Temperature
Effective projected area	0.07744 m^2

Operating and Electrical

Input Voltage	220-240 V
Line Frequency	50 or 60 Hz
Inrush current	7.8 A
Inrush time	0.01520 ms
Power Consumption	135 W
Power Factor (Fraction)	0.95
Connection	Flying leads/cables
Cable	Cable 2.0 m without plug
Number of products on MCB (16 A type B)	14
Suitable for random switching	Yes
Protection class IEC	Safety class I
Surge Protection (Common/ Differential)	Surge protection level until 1.5 kV differential mode and 1.5 kV common mode
Total harmonic distortion	20 %

Controls and Dimming

Dimmable	No
Driver/power unit/transformer	Power supply unit (On/Off)
Constant light output	No
Embedded control	-
Photocell	-

Mechanical and Housing

Housing material	Aluminium die cast
Reflector material	Polycarbonate
Optic material	Glass
Optical cover/lens material	Tempered glass
Fixation material	Steel
Housing Colour	Grey
Mounting device	Via U Shaped Bracket, Aiming Scale Angle, Universal Installation
Optical cover/lens shape	Flat
Optical cover/lens finish	Clear
Overall length	401 mm
Overall width	282 mm
Overall height	37 mm
Dimensions (height x width x depth)	37 x 282 x 401 mm
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Standard tilt angle post-top	27°
Standard tilt angle side entry	-
Optical cover type	Glass
Net Weight (Piece)	3.290 kg

Emergency Operation

Central Emergency	No

Approval and Application

Glow-wire test	Temperature 650 °C, duration 30 s
Flammability mark	For mounting on normally flammable surfaces
CE mark	Yes
ENEC mark	-
Photobiological risk	Photobiological risk group 1 @200mm to EN62778
Photobiological risk specification	0.2 m

EU RoHS compliant	Yes
Performance ambient temperature Tq	25 °C
Flickering value (PstLM)	1
Ambient temperature range	-25 to +40 °C

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Initial chromaticity	(0.440,0.403); (0.369,0.364); (0.313,0.337) SDCM<5
Power consumption tolerance	+/-10%
Init. Colour Rendering Index Tolerance	-2
Standard Deviation of Colour Matching (McAdam ellipse)	SDCM≤5

Over Time Performance (IEC Compliant)

Control gear failure rate at median useful life 50,000 h	7.5 %
Lumen maintenance (EN-IEC 62722-2-1) at median useful life* 50000 h	L80
Lumen maintenance (EN-IEC 62722-2-1) at median useful life* 75000 h	L70


Sustainability Data

Repair class	Repair Class D, this product is not designed to be repaired.
Embedded carbon (A1-A3)	29.5 kg CO_2e
Product non-virgin material ratio	26.4 %
Recyclable the content ratio of the finished product	60.8 %
GWP total B6 (kg CO2eq) Declared Unit	Please calculate using your local energy mix value: Power Declared Unit (kW) * Service life (hrs) Declared Unit * Energy mix (kg CO2eq / kwh)
GWP total B6 (kg CO2eq) Functional Unit	Please calculate using your local energy mix value: POWER DECLARED UNIT (kW) * 1000 (lm) / LUMEN OUTPUT DECLARED UNIT (lm) * 35000 (hrs) * ENERGY MIX (kg CO2 eq / kwh)
Non-virgin material ratio of the packaging	Cardboard > 80% recycled
Packaging recyclable content ratio	Cardboard recycling rate > 80%
Packaging material	Cardboard

Product Data

Order product name	BVP169 LED157/830_40_65 PSU 135W AWB
Full product name	BVP169 LED157/830_40_65 PSU 135W AWB
Full EOC	872016973613999
Order code	911401885386
Material no. (12 NC)	911401885386
Numerator – quantity per pack	1
EAN/UPC — Product/Case	8720169736139
Numerator – packs per outer box	4
EAN/UPC - Case	8720169736320

Dimensional drawing



SWB

mm	10W	20W	30W	50W	70W	100W	150W	200W
A	85	97	133	173	203	220	282	336
B	130	149	182	232	286	304	401	474
C	31	31	29	30	33	36	37	41
D	90	109	145	185	215	244	320	380
E	70	82	117	150	175	185	242	296
a	41	50	70	90	110	110	136	210
b	51	60	85	110	130	130	166	240
c	4.2	4.2	4.5	6.5	6.5	8.5	10.5	10.5
d	4.2	4.2	4.5	6.5	6.5	8.5	10.5	10.5

AWB

mm	65W	90W	135W	180W
A	203	220	282	336
B	286	304	401	474
C	33	36	37	41
D	215	244	320	380
E	175	185	242	296
a	110	110	136	210
b	130	130	166	240
c	6.5	8.5	10.5	10.5
d	6.5	8.5	10.5	10.5

Related Documents

Documents and certificates	Document Name	Download
Environmental Product Declaration	EPD-PHILIPS-BVP169-LED157-830-40-65-PSU-135W-AWB-911401885386.pdf	Download
Environmental Product Declaration	EPD-HUB-EPD-Philips-Ledinaire-All-in-floodlights-BVP169-Ref-911401885386.pdf	Download
Installation Instructions	Mounting-instruction-Ledinaire-Floodlight-All-in-AWB.pdf	Download

Photometry and lighting design	Document Name	Download
IES File	BVP169-LED157830-40-65-PSU-135W-AWB.ies	Download
LDT File	Ledinaire-Flood-BVP169-1xLED157-830-40-65-840-PSU-AWB.ldt	Download

© 2026 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.