


Photo-cell-controlled light

LN 1 LED

EAN 4007841 649715

STEINEL®
Intelligent technology



LED

long life LED
50,000 h

4,5w

4,5 W 350 lm



3000K warm-white



IP54



5 - 200 lux



IK07



Ideal 2 m



energy saving



manufacturer's
warranty
steinel.de/garantie



CE

Function description

Slim and versatile. LED, naturally. STEINEL outdoor light LN 1 LED for permanently illuminating all sides of the building at night. 4,5 W STEINEL LED lighting system, 350 lm, light comes ON automatically at dusk, including adhesive house numbers, impact-resistant material (to IK 07).

Technical specifications

Dimensions (L x W x H)	195 x 300 x 53 mm	With motion detector	No
Mains power supply	230 – 240 V / 50 – 60 Hz	Photo-cell controller	Yes
Sensor Technology	Light sensor	Twilight setting	5 – 200 lx
Output	4,5 W	Basic light level function	No
Interconnection	No	Soft light start	No
Luminous flux	350 lm	Impact resistance	IK07
Colour temperature	3000 K	IP-rating	IP54
Colour variation LED	SDCM3	Protection class	II
Colour Rendering Index CRI	80-89	Ambient temperature	-20 – 40 °C
With lamp	Yes, STEINEL LED system	Housing material	Plastic
Lamp	LED cannot be replaced	Cover material	Plastic, opal
LED life expectancy (max. °C)	50000 h	Manufacturer's Warranty	3 years
Drop in luminous flux in accordance with LM80	L70B10	includes sheet of self-adhesive numbers	Yes
Base	without	Settings via	Potentiometers
LED cooling system	Passive Thermo Control	PU1, EAN	4007841649715

<https://www.steinel.de>

Photo-cell-controlled light

LN 1 LED

EAN 4007841 649715



Dimension Drawing

