



Main

Range of product	Easergy
Product or component type	Voltage presence indicator
Device short name	VPIS V2
Mounting mode	Flush-mounted
Screw type	M3
Standards	IEC 62271-206
Phase concordance unit	VPI62421

Complementary

Cut-out dimensions	32 x 53 mm
Net weight	0,08 kg
Bulb type	LED
Height	35 mm
Width	70 mm
Depth	40 mm
Mechanical robustness	Impacts de-energized - 2 joules IEC 61958-1 Impacts de-energized - 3 impacts in the weakest places IEC 60068-2-75

Environment

Ambient air temperature for operation	-25...85 °C
Ambient air temperature for storage	-40...85 °C
Electromagnetic compatibility	Electrostatic discharge 8 kV air, 6 kV contact immunity tests-radiated disturbances) criteria B IEC 61000-4-2 Radiated radio-frequency electromagnetic field immunity test 10 V/m, 80 MHz...3 GHz immunity tests-conducted disturbances) criteria A IEC 61000-4-3 Fast transient bursts 2 kV immunity tests-conducted disturbances) criteria B IEC 61000-4-4 Damped oscillatory wave 1 kV immunity tests-conducted disturbances) criteria B IEC 61000-4-18

Packing Units

Osa tüüp pakil 1	PCE
Osade arv pakis 1	1
Pakk 1 kaal	80 g
Pakk 1 kõrgus	2,2 cm
Pakk 1 laius	8 cm
Pakk 1 pikkus	9,4 cm
Osa tüüp pakil 2	BB1
Osade arv pakis 2	14
Pakk 2 kaal	1,2 kg
Pakk 2 kõrgus	8,8 cm
Pakk 2 laius	9,3 cm
Pakk 2 pikkus	26,7 cm
Osa tüüp pakil 3	S03
Osade arv pakis 3	168
Pakk 3 kaal	14,5 kg
Pakk 3 kõrgus	30 cm
Pakk 3 laius	30 cm
Pakk 3 pikkus	40 cm

Offer Sustainability

Jätkusuutliku pakkumise olek	Green Premium toode
ELi RoHS direktiiv	Vastavus ELi RoHS deklaratsioon
Elavhõbedavaba	Jah
RoHS eranditeave	Jah
Hiina EoHS regulatsioon	Hiina RoHS deklaratsioon
Keskkonnavalade avaldus	Toote keskkonnaprofiil