

Cabinet LED luminaire with switch

Light fitting SOL1000, linear 600mm, 3000 K, opal cover

Code: SOL1000S3KO/ND

EAN: 8596099022150

This product contains a light source with energy efficiency class E



Luminaire properties

Product category:	Ceiling / wall luminaires	Effective luminous flux (lm):	1250
Luminaire efficacy (lm/W):	114	Rated lifetime L70/B50 (h):	30000
Degree of protection (IP):	IP20	Color housing:	Aluminium
Material housing:	Aluminium	Light source included:	Yes
Suitable for wall mounting:	Yes		
Suitable for surface mounting:	Yes		
Suitable for ceiling mounting:	Yes	Made in Czech republic:	Yes

Light source

Light source type:	LED	Color temperature (K):	3000
Color rendering index CRI:	80-89	Replaceability:	Removeable light source , without ballast
Light source type:	1990440183003	Energy efficiency class:	E

Optical system

Optical system:	KO	Light outlet:	Direct
Light sharing:	Symmetric	Material cover:	Plastic, opal
Radiation angle:	Extreme wide beam >80°		

Dimensions

Width (mm):	32	Height/depth (mm):	43
Built-in length (mm):	300...460	Weight (kg):	0,5

Electrical values

Protection class:	I	Connection type:	Screw terminal
Voltage type:	AC	Type of control gear:	LED operating device current-controlled
Nominal voltage (V):	220...240	Control gear included:	Yes
Type of wiring:	Ending	No dim function:	Yes