



Surface LED fitting with plastic cover - IP44

Light fitting BRSB 3x8 LED 840, opal PMMA cover, 285 mm, IP44

Code: BRSB4KO300V0/ND

EAN: 8595073794632

This product contains a light source with energy efficiency class E



Luminaire properties

Product category:	Ceiling / wall luminaires	Effective luminous flux (lm):	900
System power (W):	9	Luminaire efficacy (lm/W):	100
Rated lifetime L80/B50 (h):	80000	Degree of protection (IP):	IP44
Color housing:	White	Material housing:	Steel
Light source included:	Yes		
Suitable for wall mounting:	Yes		
Suitable for surface mounting:	Yes	Suitable for ceiling mounting:	Yes
Made in Czech republic:	Yes		

Light source

Light source type:	LED	Color temperature (K):	4000
Color rendering index CRI:	80-89	Replaceability:	Replaceable light source by professional, replaceable ballast
Light source type:	1990320184001	Energy efficiency class:	E

Optical system

Optical system:	KO	Light outlet:	Direct
Light sharing:	Symmetric	Material cover:	Plastic, opal
Radiation angle:	Open beam/diffuse		

Dimensions

Outer diameter (mm):	285	Height/depth (mm):	89
Weight (kg):	1		

Electrical values

Protection class:	I	Connection type:	Pinching contact
Voltage type:	AC	Type of control gear:	LED operating device current-controlled
Nominal voltage (V):	220...240	Control gear included:	Yes
No dim function:	Yes		