



Surface LED fitting with plastic cover - IP44

Light fitting **BRSB 3x12 LED 840, opal PMMA cover, 285 mm, IP44, sensor mw**

**Code:** BRSB4KO300V1/NDSM

**EAN:** 8595073796773



## Vlastnosti svítidla

Product category:	<b>Ceiling / wall luminaires</b>	Degree of protection (IP):	<b>IP44</b>
Color housing:	<b>White</b>	With movement sensor:	<b>Yes</b>
Material housing:	<b>Steel</b>	Suitable for wall mounting:	<b>Yes</b>
Suitable for surface mounting:	<b>Yes</b>	Suitable for ceiling mounting:	<b>Yes</b>

## Světelný zdroj

Lamp type:	<b>LED not exchangeable</b>	Effective luminous flux (lm):	<b>1400</b>
System power (W):	<b>14</b>	Luminaire efficacy (lm/W):	<b>100</b>
Color temperature (K):	<b>4000</b>	Color rendering index CRI:	<b>80-89</b>
Rated life time L80/B50 (h):	<b>80000</b>	With lamp:	<b>Yes</b>
Colour of light:	<b>White</b>		
Energy efficiency class of the built-in lamp:	<b>A++, A+, A (LED)</b>		

## Optický systém

Optical system:	<b>KO</b>	Light outlet:	<b>Direct</b>
Light sharing:	<b>Symmetric</b>	Material cover:	<b>Plastic, opal</b>
Radiation angle:	<b>Open beam/diffuse</b>		

## Rozměry

Outer diameter (mm):	<b>285</b>	Height/depth (mm):	<b>89</b>
Weight (kg):	<b>1,1</b>		

## Elektrické vlastnosti

Protection class:	<b>I</b>	Connection type:	<b>Pinching contact</b>
Voltage type:	<b>AC</b>	Type of control gear:	<b>LED operating device current-controlled</b>
Nominal voltage (V):	<b>220...240</b>	Control gear included:	<b>Yes</b>
No dim function:	<b>Yes</b>		