



Recessed LED fitting with cover

MODUS IBP4000, IP54, recessed into raster - modul 600, square A, opal cover, LED 840, NONSELV, non-dimmable driver

Code: IBP4000A4KO600ND

EAN: 8596099014933

This product contains a light source with energy efficiency class D



Luminaire properties

Product category:	Ceiling / wall luminaires	Effective luminous flux (lm):	4100
System power (W):	32	Luminaire efficacy (lm/W):	128
Rated lifetime L80/B50 (h):	80000	Degree of protection (IP):	IP54
Color housing:	White	Material housing:	Steel
Light source included:	Yes		
Suitable for built-in mounting:	Yes		
Made in Czech republic:	Yes	Degree of protection II (IP):	IP20

Light source

Light source type:	LED	Color temperature (K):	4000
Color rendering index CRI:	80-89	Replaceability:	Removeable light source, removeable ballast
Light source type:	1990200484002	Energy efficiency class:	D

Optical system

Optical system:	KO	Light outlet:	Direct
Light sharing:	Symmetric	Material cover:	Plastic, opal
Radiation angle:	Extreme wide beam >80°		

Dimensions

Length (mm):	596	Width (mm):	596
Height/depth (mm):	90	Built-in height/depth (mm):	90
Raster (mm):	600	Size version:	S
Weight (kg):	3		

Electrical values

Protection class:	I	Connection type:	Pinching contact
Voltage type:	AC	Type of control gear:	LED operating device current-controlled
Nominal voltage (V):	220...240	Control gear included:	Yes
No dim function:	Yes		