



Main

Range of product	Mureva Styl
Product or component type	Mounting box
Range compatibility	enclosure
Colour tint	Grey (RAL 7016)

Complementary

Device mounting	Surface
Number of gangs	1 gang
Cable entry	Easy valve access
Condition of use	Indoor/outdoor
Material	PP (polypropylene) SEBS
Length	76 mm
Height	54 mm
Width	76 mm
Depth	54 mm
Chemical and detergent products resistance	Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane

Environment

Quality labels	AENOR NF
IP degree of protection	IP55
IK degree of protection	IK08
Flame retardance	Self-extinguishing 650 °C conforming to IEC 60695-2-1
Ambient air temperature for operation	-5...40 °C
Ambient air temperature for storage	-25...55 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	71.0 g
Package 1 Height	7.6 cm
Package 1 width	5.4 cm

Package 1 Length	7.6 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	803.0 g
Package 2 Height	8.0 cm
Package 2 width	16.0 cm
Package 2 Length	39.5 cm
Unit Type of Package 3	P12
Number of Units in Package 3	240
Package 3 Weight	35.68 kg
Package 3 Height	50.0 cm
Package 3 width	80.0 cm
Package 3 Length	120.0 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile