



## DEVIpipeline™ 10 V2

The DEVIpipeline™ 10 V2 is a self-limiting heating cable that is used for frost protection of pipes.

The self-limiting capability of the cable ensures that the output of the cable increase or decrease according to ambient temperature.

The heating cables can be installed outside water pipes. The product range: drum cable, cable with cold lead without mains plug and cable with cold lead mains plug.

The product range: drum cable and cable with cold lead mains plug. All self-limiting heating cables must be over-temperature protected by a thermostat, as the output will decrease, but never be zero, and be protected by a RCD with a maximum trip current of 30 mA.

**Note 1:** The cable is not approved for installation inside the water pipe and for use in contact with drinking water or water for human consumption, waste water, etc.

**Note 2:** It is the full responsibility of the installer/designer to use proper cold lead dimensioned for the purpose and assembly sets that establish sufficient mechanical strength, flammability resistance and water tightness - and to design the heating unit with correct output for the specific application to avoid overheating of the cable or building materials.

### Benefits:

- Cut to length on site
- Ready-made lengths
- Small cable size

### Standard compliance:

- IEC 60335-1:2012

### Approvals:



Type	Value
Nominal voltage	230 V~
Nominal output (min-max):	10 W/m @ 10 °C (8,5-13,5 W/m @ 10 °C)
Max. permissible use temperature, powered	65 °C
Max. permissible use temperature, unpowered	65 °C
Minimum installation temperature	- 5 °C
Heating cable dimensions	7,8 x 5,3 mm
Outer sheath	Blue, TPE
Minimum Screen Coverage	100% aluminium foil
Maximum resistance protective braid	18,2 Ω/Km
Bending radius, min.	25 mm (inside of the cable)
Cold lead with plug	2 m, 3 x 0,75 mm <sup>2</sup> , types: with Schuko plug and with Danish plug
IP Class	IPX7

### Types: Drum

Item no.	Length	Min-max length per drum	Number of length allowed on drum, max	Nominal output @ 10 °C	EAN no.
98300016	Drum, 100 m	100 m	1	10 W/m	5703466217771
98300015	Drum, 300 m	300 m	1	10 W/m	5703466217764
98300017	Drum, 1000 m	1000 m	1	10 W/m	5703466217788
98300019	Cut-to-length	1 – 1000 m	1 / 2	10 W/m	5703466217801

### Types: Ready-made with Schuko plug

Item no.	Length	Nominal output @ 10 °C	Cold lead	EAN no.
98300071	2 m	20 W	2 m	5703466217924
98300072	4 m	40 W	2 m	5703466217931
98300073	6 m	60 W	2 m	5703466217948
98300074	8 m	80 W	2 m	5703466217955
98300075	10 m	100 W	2 m	5703466217962
98300076	12 m	120 W	2 m	5703466217979
98300077	14 m	140 W	2 m	5703466217986
98300078	16 m	160 W	2 m	5703466217993
98300079	19 m	190 W	2 m	5703466218006
98300080	22 m	220 W	2 m	5703466218013
98300081	25 m	250 W	2 m	5703466218020

### Types: Ready-made with plug, Danish version

Item no.	Length	Nominal output @ 10 °C	Cold lead	EAN no.
98300082	2 m	20 W	2 m	5703466218037
98300083	4 m	40 W	2 m	5703466218044
98300084	6 m	60 W	2 m	5703466218051
98300085	8 m	80 W	2 m	5703466218068
98300086	10 m	100 W	2 m	5703466218075
98300087	12 m	120 W	2 m	5703466218082
98300088	14 m	140 W	2 m	5703466218099
98300089	16 m	160 W	2 m	5703466218105
98300090	19 m	190 W	2 m	5703466218112
98300091	22 m	220 W	2 m	5703466218129
98300092	25 m	250 W	2 m	5703466218136

### Maximum heating circuit length on a pipe, with circuit breaker with C-characteristic

Switch on temperature	DEVipeheat™ 10 V2	
	10 A	16 A
10 °C	100 m	-
0 °C	96 m	-
-20 °C	77 m	-

### Power output characteristic

Output of heating cable installed and measured on a pipe.

