

# ENSTO

Küttekaabel

TASSU200W9M

Tüüp TASSU200W9M  
 GTIN 6438100353896  
 Nimi Küttekaabel Tassu

Preterminated twin-conductor cable with a PVC sheath. The lowest installation temperature is -5 °C. The output of the cable is 20W/m.

**Kirjeldus** TASSU underfloor heating cables for a direct or partial storage floor heating. The direct underfloor heating is used in wet or damp areas, where the floor material is low thermal resistant, e.g. clinker. The direct underfloor heating is suitable also in other areas as the only heating form. The partial storage underfloor heating is used for example in living rooms and kitchens. The output per square meter should be 80-150 W/m<sup>2</sup>, the installation distance 13-25cm and the installation depth 5-10cm.

**Müüja** Ensto Building Systems Finland Oy



## Spetsifikatsioon

### Mõõtmed

Põranda pindala: 1,3 ... 2,5 m<sup>2</sup>  
 Kaabli pikkus: 9 m  
 Net Weight: 1,01 kg

### Elektrilised väärtused

Nimipinge: 230 V  
 Võimsus: 200 W  
 Võimsus/m (W/m): 20 W/m  
 Võimsus (W/m<sup>2</sup>): 80 ... 150 W/m<sup>2</sup>  
 Resistance: 264,5 Ω  
 Töösagedus: 50 Hz

## Muu

ETIM Class: EC000339

## ETIM Technical specification

---

### etim

Cable type: Dual core  
Max. hold temperature: 70 °C  
Heating capacity: 20 W  
Screening: None  
Nominal voltage: 230 V  
Height: 4,9 mm  
Width: 7,8 mm  
Length: 9 m  
Colour: Red  
Application: Other

## Pakend

---

### Pakendatud alusele

Pakendi suurus: 68 pcs  
Sügavus: 1200 mm  
Laius: 800 mm  
Kõrgus: 1098 mm

### Standard pakend

Pakendi suurus: 1 pce  
Sügavus: 417 mm  
Laius: 383 mm  
Kõrgus: 79 mm  
Kaal: 1,331 kg  
Kogus: 12,617169 l