

ENSTO

Küttekaabel

TASSU800W38M

Tüüp TASSU800W38M

GTIN 6438100353988

Nimi Küttekaabel Tassu

Preterminated twin-conductor cable with a PVC sheath. The lowest installation temperature is -5 °C. The output of the cable is 20W/m.

Kirjeldus TASSU underfloor heating cables for a direct or partial storage floor heating. The direct underfloor heating is used in wet or damp areas, where the floor material is low thermal resistant, e.g. clinker. The direct underfloor heating is suitable also in other areas as the only heating form. The partial storage underfloor heating is used for example in living rooms and kitchens. The output per square meter should be 80-150 W/m², the installation distance 13-25cm and the installation depth 5-10cm.

Müüja Ensto Building Systems Finland Oy



Spetsifikatsioon

Mõõtmed

| | |
|------------------|---------------------------|
| Põranda pindala: | 5,3 ... 10 m ² |
| Kaabli pikkus: | 38 m |
| Net Weight: | 2,45 kg |

Elektrilised väärtused

| | |
|------------------------------|-----------------------------|
| Nimipinge: | 230 V |
| Võimsus: | 800 W |
| Võimsus/m (W/m): | 20 W/m |
| Võimsus (W/m ²): | 80 ... 150 W/m ² |
| Resistance: | 66,1 Ω |
| Töösagedus: | 50 Hz |

Muu

ETIM Class: EC000339

ETIM Technical specification

etim

Cable type: Dual core
Max. hold temperature: 70 °C
Heating capacity: 20 W
Screening: None
Nominal voltage: 230 V
Height: 4,9 mm
Width: 7,8 mm
Length: 38 m
Colour: Red
Application: Other

Pakend

Pakendatud alusele

Pakendi suurus: 68 pcs
Sügavus: 1200 mm
Laius: 800 mm
Kõrgus: 1098 mm

Standard pakend

Pakendi suurus: 1 pce
Sügavus: 417 mm
Laius: 383 mm
Kõrgus: 79 mm
Kaal: 2,771 kg
Kogus: 12,617169 l