

DROP 22 LED

Part number 3109456



Description

Series of wall and ceiling mounted luminaire for indoor and outdoor, comprising::

- Satin pressed glass diffuser, internally coated, for homogeneous light distribution
- Technopolymer housing
- Aluminium reflector
- Technopolymer silicone sealing gasket
- Chromed steel spring locks to secure the diffuser to housing
- Integral, tiltable, self-heat dissipating, Metal-Core SMD LED board (future proof)
- Toolless glass diffuser opening: quick to install and easy to maintain, helping to save time and reduce servicing costs
- Hyper-frequency (HF) sensor operating at 5.8 Ghz+/- 75 Mhz
- The integral sensor' protection module grants no reciprocal interference between multiple luminaires in one area
- Widest detection field up to 8 m
- Side entry for 20 mm conduits (drill out holes in housing arrangement)
- Self-adhesive pictograms available as accessory (ordered separately)
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08
- Design by ROBERTO FIORATO

To maintain the regular updating of our products, PERFORMANCE IN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25°C. Terms of warranty are available at www.performanceinlighting.com/qr/qr/company/terms-and-conditions

Product data

ETIM Group:	EG000027	ETIM Class:	EC0028g2
-------------	----------	-------------	----------

General information

Lampholder:	LED	Light source:	LED
Lightsource lumen output [lm]:	1214	Luminaire lumen output [lm]:	758
Luminaire wattage [W]:	11 W	Luminous efficacy [lm/W]:	69
CRI:	80	Kelvin:	3000
Colour / Finish:	BK-81 / Black / Textured	IP degree of protection:	IP55
IK-J-xxIP:	IK06 1J xx3	Insulation class:	II
Optic:	SYMMETRIC EXTRA-WIDE	Net weight [kg]:	1.741

Mechanical features

Shape:	ROUND $150 \leq X \leq 300$ MM	Housing material:	PLASTIC
Diffuser material:	GLASS	Glow wire test [°C]:	750 °C

Electrical features

Voltage type:	AC/DC	Power factor / COS Φ :	>0.9
Inrush current [A/ μ s]:	5 / 50		

Installation

Application area:	Outdoor	Mounting type:	Wall / Ceiling surface
Min. ambient temperature [°C]:	-25	Max. ambient temperature [°C]:	25
Min. distance from lighted object [m]:	0.00		

Light features

MacAdam:	3	Lumen maintenance:	L80B10@50000h
Distribution of light emission:	Direct		

To maintain the regular updating of our products, PERFORMANCE IN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25°C. Terms of warranty are available at www.performanceinlighting.com/qr/qr/company/terms-and-conditions

