

# ENSTO

Küttekaabel

TASSUS165W16M

Tüüp TASSUS165W16M

GTIN 6438100354138

Nimi Küttekaabel TassuS

Preterminated twin-conductor cable with a PVC sheath. The lowest installation temperature is -5 °C. The output of the cable is 10W/m.

**Kirjeldus** TASSU S underfloor heating cables are used in plasterboard floors, wooden floors and in renovation, where the cable is installed on top of the old floor. The output per square meter should be 60 – 110 W/m<sup>2</sup>, the installation distance 9 – 17cm and the installation depth 2.5cm. The lowest installation temperature is -10 °C.

**Müüja** Ensto Building Systems Finland Oy



## Spetsifikatsioon

### Mõõtmed

Põranda pindala:	1,5 ... 2,8 m <sup>2</sup>
Kaabli pikkus:	16 m
Net Weight:	1,3 kg

### Elektrilised väärtused

Nimipinge:	230 V
Võimsus:	165 W
Võimsus/m (W/m):	10 W/m
Võimsus (W/m <sup>2</sup> ):	60 ... 110 W/m <sup>2</sup>
Resistance:	320,6 Ω
Töösagedus:	50 Hz

### Muu

ETIM Class:	EC000339
-------------	----------

## ETIM Technical specification

---

### etim

Cable type:	Dual core
Max. hold temperature:	70 °C
Heating capacity:	10 W
Screening:	None
Nominal voltage:	230 V
Height:	4,9 mm
Width:	7,8 mm
Length:	16 m
Colour:	Red
Application:	Other

### Pakend

---

#### Pakendatud alusele

Pakendi suurus:	68 pcs
Sügavus:	1200 mm
Laius:	800 mm
Kõrgus:	1098 mm

#### Standard pakend

Pakendi suurus:	1 pce
Sügavus:	417 mm
Laius:	383 mm
Kõrgus:	79 mm
Kaal:	1,621 kg
Kogus:	12,617169 l