

ENSTO

Küttekaabel

TASSUS250W25M



Tüüp TASSUS250W25M

GTIN 6438100354046

Nimi Küttekaabel TassuS

Preterminated twin-conductor cable with a PVC sheath. The lowest installation temperature is $-5\text{ }^{\circ}\text{C}$. The output of the cable is 10 W/m .

Kirjeldus TASSU S underfloor heating cables are used in plasterboard floors, wooden floors and in renovation, where the cable is installed on top of the old floor. The output per square meter should be $60 - 110\text{ W/m}^2$, the installation distance $9 - 17\text{ cm}$ and the installation depth 2.5 cm . The lowest installation temperature is $-10\text{ }^{\circ}\text{C}$.

Müüja Ensto Building Systems Finland Oy

Spetsifikatsioon

Mõõtmed

Põranda pindala: 2,3 ... 4,2 m²

Kaabli pikkus: 25 m

Net Weight: 1,81 kg

Elektrilised väärtused

Nimipinge: 230 V

Võimsus: 250 W

Võimsus/m (W/m): 10 W/m

Võimsus (W/m²): 60 ... 110 W/m²

Resistance: 211,6 Ω

Töösagedus: 50 Hz

Muu

ETIM Class: EC000339

ETIM Technical specification

etim

| | |
|------------------------|-----------|
| Cable type: | Dual core |
| Max. hold temperature: | 70 °C |
| Heating capacity: | 10 W |
| Screening: | None |
| Nominal voltage: | 230 V |
| Height: | 4,9 mm |
| Width: | 7,8 mm |
| Length: | 25 m |
| Colour: | Red |
| Application: | Other |

Pakend

Pakendatud alusele

| | |
|-----------------|---------|
| Pakendi suurus: | 68 pcs |
| Sügavus: | 1200 mm |
| Laius: | 800 mm |
| Kõrgus: | 1098 mm |

Standard pakend

| | |
|-----------------|-------------|
| Pakendi suurus: | 1 pce |
| Sügavus: | 417 mm |
| Laius: | 383 mm |
| Kõrgus: | 79 mm |
| Kaal: | 2,131 kg |
| Kogus: | 12,617169 l |