

ENSTO

Küttekaabel

TASSUS300W29M



Tüüp TASSUS300W29M

GTIN 6438100354053

Nimi Küttekaabel TassuS

Preterminated twin-conductor cable with a PVC sheath. The lowest installation temperature is $-5\text{ }^{\circ}\text{C}$. The output of the cable is 10 W/m .

Kirjeldus TASSU S underfloor heating cables are used in plasterboard floors, wooden floors and in renovation, where the cable is installed on top of the old floor. The output per square meter should be $60 - 110\text{ W/m}^2$, the installation distance $9 - 17\text{ cm}$ and the installation depth 2.5 cm . The lowest installation temperature is $-10\text{ }^{\circ}\text{C}$.

Müüja Ensto Building Systems Finland Oy

Spetsifikatsioon

Mõõtmed

Põranda pindala: 2,7 ... 5 m²

Kaabli pikkus: 29 m

Net Weight: 2,05 kg

Elektrilised väärtused

Nimipinge: 230 V

Võimsus: 300 W

Võimsus/m (W/m): 10 W/m

Võimsus (W/m²): 60 ... 110 W/m²

Resistance: 176,3 Ω

Töösagedus: 50 Hz

Muu

ETIM Class: EC000339

ETIM Technical specification

etim

Cable type:	Dual core
Max. hold temperature:	70 °C
Heating capacity:	10 W
Screening:	None
Nominal voltage:	230 V
Height:	4,9 mm
Width:	7,8 mm
Length:	29 m
Colour:	Red
Application:	Other

Pakend

Pakendatud alusele

Pakendi suurus:	68 pcs
Sügavus:	1200 mm
Laius:	800 mm
Kõrgus:	1098 mm

Standard pakend

Pakendi suurus:	1 pce
Sügavus:	417 mm
Laius:	383 mm
Kõrgus:	79 mm
Kaal:	2,371 kg
Kogus:	12,617169 l