

ENSTO

Küttekaabel

TASSUS600W59M



Tüüp	TASSUS600W59M
GTIN	6438100354084
Nimi	Küttekaabel TassuS
	Preterminated twin-conductor cable with a PVC sheath. The lowest installation temperature is -5 °C. The output of the cable is 10W/m.
Kirjeldus	TASSU S underfloor heating cables are used in plasterboard floors, wooden floors and in renovation, where the cable is installed on top of the old floor. The output per square meter should be 60 – 110 W/m ² , the installation distance 9 – 17cm and the installation depth 2.5cm. The lowest installation temperature is -10 °C.
Müüja	Ensto Building Systems Finland Oy

Spetsifikatsioon

Mõõtmed

Põranda pindala:	5,5 ... 10 m ²
Kaabli pikkus:	59 m
Net Weight:	3,76 kg

Elektrilised väärtused

Nimipinge:	230 V
Võimsus:	600 W
Võimsus/m (W/m):	10 W/m
Võimsus (W/m ²):	60 ... 110 W/m ²
Resistance:	88,2 Ω
Töösagedus:	50 Hz

Muu

ETIM Class:	EC000339
-------------	----------

ETIM Technical specification

etim

Cable type:	Dual core
Max. hold temperature:	70 °C
Heating capacity:	10 W
Screening:	None
Nominal voltage:	230 V
Height:	4,9 mm
Width:	7,8 mm
Length:	59 m
Colour:	Red
Application:	Other

Pakend

Pakendatud alusele

Pakendi suurus:	36 pcs
Sügavus:	1200 mm
Laius:	800 mm
Kõrgus:	1038 mm

Standard pakend

Pakendi suurus:	1 pce
Sügavus:	399 mm
Laius:	148 mm
Kõrgus:	398 mm
Kaal:	4,138 kg
Kogus:	23,502696 l