

# ENSTO

Küttekaabel

TASSUS700W71M



Tüüp	TASSUS700W71M
GTIN	6438100354091
Nimi	Küttekaabel TassuS
	Preterminated twin-conductor cable with a PVC sheath. The lowest installation temperature is -5 °C. The output of the cable is 10W/m.
Kirjeldus	TASSU S underfloor heating cables are used in plasterboard floors, wooden floors and in renovation, where the cable is installed on top of the old floor. The output per square meter should be 60 – 110 W/m <sup>2</sup> , the installation distance 9 – 17cm and the installation depth 2.5cm. The lowest installation temperature is -10 °C.
Müüja	Ensto Building Systems Finland Oy

## Spetsifikatsioon

### Mõõtmed

Põranda pindala:	6,4 ... 11,7 m <sup>2</sup>
Kaabli pikkus:	71 m
Net Weight:	4,37 kg

### Elektrilised väärtused

Nimipinge:	230 V
Võimsus:	700 W
Võimsus/m (W/m):	10 W/m
Võimsus (W/m <sup>2</sup> ):	60 ... 110 W/m <sup>2</sup>
Resistance:	75,6 Ω
Töösagedus:	50 Hz

### Muu

ETIM Class:	EC000339
-------------	----------

## ETIM Technical specification

---

### etim

Cable type:	Dual core
Max. hold temperature:	70 °C
Heating capacity:	10 W
Screening:	None
Nominal voltage:	230 V
Height:	4,9 mm
Width:	7,8 mm
Length:	71 m
Colour:	Red
Application:	Other

### Pakend

---

#### Pakendatud alusele

Pakendi suurus:	36 pcs
Sügavus:	1200 mm
Laius:	800 mm
Kõrgus:	1038 mm

#### Standard pakend

Pakendi suurus:	1 pce
Sügavus:	399 mm
Laius:	148 mm
Kõrgus:	398 mm
Kaal:	4,748 kg
Kogus:	23,502696 l