

ENSTO

Kombineeritud termostaat

ECO16BT-J



Tüüp	ECO16BT-J
GTIN	6438100339081
Nimi	Kombineeritud termostaat ECO Kahe anduriga pörandaküttetermostaat 3600W IP30
Kirjeldus	Kaksitermostaat eluruumide pörandakütte juhtimiseks. Võimalik juhtida nii manuaalselt kui Bluetooth ühenduse abil läbi Ensto Heat Control mobiiliäpi (Android ja iOS). Komplektis termostaat, pörandaadur, Jussi sarja keskplaat ja katteraam. Ruumiandur sisseehitatud.
Müüja	Ensto Building Systems Finland Oy

Spetsifikatsioon

Mõõtmed

Pikkus:	48 mm
Laius:	85 mm
Mõõtmed p x l x k:	48 x 85 x 85 mm
Kõrgus:	85 mm
Net Weight:	0,132 kg

Elektrilised väärtused

Võimsus:	3600 W
Nimipinge:	230 V
Nimivool:	16 A
Töösagedus:	50 Hz

Kaitseastmed

Kaitseaste:	IP30
Kaitseaste:	II

Muu

ETIM Class:	EC011309
-------------	----------

ETIM Technical specification

etim

Type of power supply:	230 V
Connection:	Wireless
With receiver:	No
Measuring range:	5 ... 50 °C
External sensor:	No
With thermal feedback:	No
Control characteristic:	Other
Heating:	No
Number of heater outputs:	1
Suitable for cooling:	No
Number of cooler outputs:	0
Differential value:	1 K
Adjustable differential:	No
Selector switch for heating and heating with hot water:	No
Sensor/feeler type:	Resistance sensor
Temperature readable:	No
With display:	No
Type of clock:	Week clock
Clock model:	Digital
Overtime switch:	No
Optimisation:	No
With tap water circuit:	No
Operation:	Turn
Weather-dependent control system:	No
Number of switching programmes:	10
Max. contact voltage:	253 V
Max. contact load:	16 A
Degree of protection (IP):	IP30
Degree of protection (NEMA):	2
Explosion-proof:	No
Colour:	White
Width:	85 mm
Depth:	48 mm
Height:	85 mm
Class of the temperature control:	II
Standby power consumption (solstandby):	0,5 W
etim7.EF014925:	No
etim7.EF014926:	No
etim7.EF014927:	No

Pakend

Pakendatud alusele

Pakendi suurus:	540 pce
Sügavus:	1200 mm
Laius:	800 mm
Kõrgus:	1015 mm

Standard pakend

Pakendi suurus:	1 pce
Sügavus:	122 mm
Laius:	104 mm
Kõrgus:	64 mm
Kaal:	0,166 kg
Kogus:	0,812032 l