

# Bare copper conductor

35 mm<sup>2</sup> Bare Cu-conductor

Nexans Ref.: 26004898

Country Ref.: 0622435

Cu-conductor for use in the network as earthconductor

## DESCRIPTION

Bare copper wire with resistance according to IEC 60228. In order to facilitate siting, the copper wire is annealed.



## STANDARDS

International IEC 60228

## CHARACTERISTICS

### Construction characteristics

Conductor flexibility	Class 2
Conductor material	Bare copper
Conductor shape	Circular compacted
Number of conductors	1

### Dimensional characteristics

Approximate weight	301 kg/km
Conductor cross-section	35 mm <sup>2</sup>
Nominal outer diameter	7.4 mm

### Electrical characteristics

Max. DC resistance of the conductor at 20°C	0.524 Ohm/km
---	--------------

### Usage characteristics

Adaptor	-
Element length	- m
Length	500 m
Packaging	K6
Short-circuit max. conductor temperature	370 °C



Conductor flexibility  
Class 2

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

Generated 11/14/22 www.nexans.se Page 1 / 1